

LTPD01

Outdoor PTZ Dome Housing

12.7 cm (5 in), PTZ speed dome housing



Model	LTPD01
Standard Setting	Available with BNC cable
OSD menu	Available
Preset	Up to 226 preset positions, 8 scanning modes
Surge Protection	-
Dimensions (W × H × L)	262 mm × 382.7 mm × 150 mm (10.3 in × 15.1 in × 5.9 in)
Weight	3 kg (6.61 lb)
Wavelength	850 nm
Illumination Distance	100 m (328.1 ft)
Beam Angle	-
LEDs	9 pieces
LED Lifetime	> 25,000 hours
Light On/Off	On when illumination is lower than 4 lux
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-6P enclosure rating
- Die-cast aluminum construction

Tech Specs

Model	LTPD01
Type	Indoor/Outdoor
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Die-cast aluminum
Finish	White
Input Power	12 V DC
Power Consumption	50 W
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Pan Speed	0° to 300° per second
Tilt Range (Movement in Vertical Plane)	-45° to 45°
Tilt Speed	0 to 270° per second
Accuracy	0.225° ± 0.003°
Atmospheric Pressure	-
Operating Ambient Temperature	-10 °C to 50 °C (-14 °F to 122 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Communication Speed	2,400 bps, 4,800 bps, 9,600 bps adjustable