

LTPD02

Outdoor PTZ Dome Housing

20.8 cm (8.2 in), PTZ speed dome housing



Model	LTPD02
Standard Setting	Available with BNC cable
OSD menu	Available
Preset	Up to 160 preset positions, 1 scanning modes, 4 tracks (path record), 8 patro groups (each patrol group patrol point 2 to 64)
Surge Protection	-
Dimensions (W × H × L)	208 mm × 433 mm × 278 mm (8.2 in × 17.0 in × 10.9 in)
Internal Usable Size (W × H × L)	55 mm × 60 mm × 120 mm (2.2 in × 2.4 in × 4.7 in)
Weight	3 kg (6.6 lb)
Wavelength	850 nm
Illumination Distance	2 m to 120 m (6.6 ft to 393.7 ft), 1 way short distance, 2 way long distance LED
Beam Angle	-
LEDs	9 pieces
LED Lifetime	> 25,000 hours
Light On/Off	On when illumination is lower than 4 lux
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-6P enclosure rating
- Die-cast aluminum construction

Tech Specs

Model	LTPD02
Type	Indoor/Outdoor
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Die-cast aluminum, ABS
Finish	White
Input Power	12 V DC
Power Consumption	30 W maximum
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Pan Speed	0.5 to 160° per second
Tilt Range (Movement in Vertical Plane)	0° to 90°
Tilt Speed	0.5 to 30° per second
Accuracy	0.1°
Atmospheric Pressure	-
Operating Ambient Temperature	-10 °C to 50 °C (-14 °F to 122 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication Protocols	RS-485, LAN
Communication Speed	Pelco-D (9600 bps), 2,400 bps, 4,800 bps, 9,600 bps adjustable