

LTSV02

Anti-vibration White light PTZ Camera

IP66, anti-vibration design suitable for vehicle use, white light illumination with distance up to 400 m (1312.3 ft), wiper included

Model	LTSV02
Operating Ambient Temperature	-31 to 65 °C (-31 °F to 149 °F)
Communication	RS-485
Protocols	Pelco-D/Pelco-P
Baud Rate	2,400/4,800/9,600/19,200 bps adjustable
Dimensions (W × H × L)	235 mm × 176 mm × 375 mm (9.25 in × 6.93 in × 14.76 in)
Weight	7.2 kg (15.87 lb)
Colour Temperature	6000 K
Wavelength	-
Illumination Distance	400 m (1312.3 ft)
Beam angle	6° to 60°

*Design and specifications are subject to change without prior notice.



Features

- IP66, NEMA-6P enclosure rating
- Anti-vibration design suitable for vehicle use
- Built-in white light illuminator with distance up to 400 m (1312.3 ft)
- Pan and tilt speed adjustable
- Wiper included

Tech Specs

Model	LTSV02
Type	Indoor/Outdoor, anti-vibration
Protection Rating	IP66, NEMA-4X enclosure rating
Material	High-strength aluminum
Finish	Silver
Input Power	10.5 V DC to 18 V DC (3.5 A)
Power Consumption	28 W
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Pan Speed	<ul style="list-style-type: none"> ▪ 0° to 80° per second adjustable ▪ Preset speed: 0° to 80° per second adjustable
Tilt Range (Movement in Vertical Plane)	-90° to 90°
Tilt Speed	<ul style="list-style-type: none"> ▪ 0° to 40° per second adjustable ▪ Preset speed: 100° per second
Accuracy	0.225° ± 0.003°
Atmospheric Pressure	80 kPa to 106 kPa
Relative Humidity	5 % to 95 % noncondensing