

# LTEV14ST

## LTEV14ST Caixa para câmera térmica IP67

Construção em alumínio fundido, suporte de montagem na parede, tamanho interno utilizável (L x A x C): 100 mm x 70 mm x 380 mm



### Features

- IP67, NEMA-6 enclosure rating
- Designed for indoor and outdoor applications
- Input power: 12 V DC/24 V AC/110 V AC/220 V AC (available) or PoE (upgradable)
- Included wiper and sunshield (optional)
- Built-in heater and blower (optional)
- Adjustable sliding camera tray
- Die-cast aluminum construction
- High impact resistance

### Available Models

Model	Sunshield	Wiper	Front Window
LTEV14			Glass
LTEV14S	+		Glass
LTEV14W		+	Glass
LTEV14SW	+	+	Glass
LTEV14T			Hole (for Thermal Camera)
LTEV14TG			Germanium Glass (for Thermal Camera)
LTEV14ST	+		Hole (for Thermal Camera)
LTEV14STG	+		Germanium Glass (for Thermal Camera)

\*The different accessories in above table have the following models available.

Model	Illumination	Heater	Blower	Input Power
LTEV14-0				
LTEV14-1-1		+		12 V DC
LTEV14-1-2		+		24 V AC
LTEV14-1-3		+		110 V AC
LTEV14-1-4		+		220 V AC
LTEV14-2-1			+	12 V DC
LTEV14-2-2			+	24 V AC
LTEV14-2-3			+	110 V AC
LTEV14-2-4			+	220 V AC
LTEV14-3-1		+	+	12 V DC
LTEV14-3-2		+	+	24 V AC
LTEV14-3-3		+	+	110 V AC
LTEV14-3-4		+	+	220 V AC
LTEV14-3-5		+	+	PoE

### Tech Specs

Model	LTEV14
<b>Type</b>	Indoor/Outdoor, side opening
<b>Protection Rating</b>	IP67, NEMA-6 enclosure rating
<b>Material</b>	Die-cast aluminum
<b>Finish</b>	White polyester powder coat
<b>Input Power</b>	<ul style="list-style-type: none"> <li>• 12 V DC (LTEV14-1-1, LTEV14-2-1, LTEV14-3-1)</li> <li>• 24 V AC (LTEV14-1-2, LTEV14-2-2, LTEV14-3-2)</li> <li>• 110 V AC (LTEV14-1-3, LTEV14-2-3, LTEV14-3-3)</li> <li>• 220 V AC (LTEV14-1-4, LTEV14-2-4, LTEV14-3-4)</li> <li>• PoE (IEEE 802.3at Class 4 PoE Plus compliant) (LTEV14-3-5)</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Heater (24 V AC): 6 W (250 mA)</li> <li>• Heater (220 V AC): 5.3 W (23 mA)</li> <li>• Heater (12 V DC): 4.2 W (350 mA)</li> <li>• Blower: 1.8 W (150 mA)</li> </ul>
<b>Network Interface</b>	RJ-45 x 2 (PoE input/data output) (LTEV14-3-5)
<b>Dimensions (W x H x L)</b>	185 mm x 134 mm x 496 mm (7.3 in x 5.3 in x 19.5 in)
<b>Window Viewing Area (W x H)</b>	100 mm x 70 mm (3.9 in x 2.8 in)
<b>Window Thickness</b>	3 mm (0.12 in), tempered glass
<b>Internal Usable Size<sup>2</sup> (W x H x L)</b>	<ul style="list-style-type: none"> <li>• 100 mm x 70 mm x 380 mm (3.9 in x 2.8 in x 15.0 in) (LTEV14-0)</li> <li>• 100 mm x 70 mm x 330 mm (3.9 in x 2.8 in x 13.0 in) (LTEV14-1-1, LTEV14-1-2, LTEV14-1-3, LTEV14-1-4, LTEV14-2-1, LTEV14-2-2, LTEV14-2-3, LTEV14-2-4, LTEV14-3-1, LTEV14-3-2, LTEV14-3-3, LTEV14-3-4)</li> <li>• 100 mm x 70 mm x 330 mm (3.9 in x 2.8 in x 13.0 in) (LTEV14-0-5, LTEV14-1-5, LTEV14-3-5)</li> </ul>
<b>Heater Control</b>	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) ( LTEV14-1-1, LTEV14-1-2, LTEV14-1-3, LTEV14-1-4, LTEV14-3-1, LTEV14-3-2, LTEV14-3-3, LTEV14-3-4, LTEV14-1-5, LTEV14-3-5)
<b>Blower Control</b>	On at 35 °C ± 3 °C (95 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) ( LTEV14-2-1, LTEV14-2-2, LTEV14-3-2, LTEV14-2-4, LTEV14-3-1, LTEV14-3-2, LTEV14-3-3, LTEV14-3-4, LTEV14-3-5)
<b>Operating Ambient Temperature</b>	-40 °C to 60 °C (-40 °F to 140 °F)
<b>Weight</b>	3.6 kg (7.94 lb)
<b>Certifications</b>	CE, FCC, RoHS
<b>Related Products</b>	-

1. The specs for LTEV14-\_-\_-\_, LTEV14S-\_-\_-\_, LTEV14W-\_-\_-\_ and LTEV14SW-\_-\_-\_ are the same as LTEV14-0, LTEV14S-0, LTEV14W-0 and LTEV14SW-0.

\*Design and specifications are subject to change without prior notice.

