

# LTAK08

## Painel de controle



### Features

- Support Pelco-P/Pelco-D
- Joystick for accurate control
- LCD Display
- Alarm function and shortcut key available

### Tech Specs

|                                      |  |
|--------------------------------------|--|
| <b>Model</b>                         | LTAK08   |
| <b>Operating Ambient Temperature</b> | -10 °C to 50 °C (14 °F to 122 °F)                      |
| <b>Relative Humidity</b>             | 5 % to 95 % noncondensing                              |
| <b>Interface Connector</b>           | 6 pins interface, DB 9 pins female outlet              |
| <b>Communication Baud Rate</b>       | 1,200 bps, 2,400 bps, 4,800 bps, 9,600 bps, 19,200 bps |
| <b>Communication Protocols</b>       | RS-485<br>Pelco-D, Pelco-P                             |
| <b>Transmission Distance</b>         | 1200 m (3937 ft)                                       |
| <b>Input Power</b>                   | 12 V DC  |
| <b>Power Consumption</b>             | 6 W  |
| <b>Dimensions (L x W x H)</b>        | 306 mm x 150 mm x 99 mm (12.0 in x 5.9 in x 3.9 in)    |
| <b>Weight</b>                        | 1.3 kg (2.9 lb)  |

\*Design and specifications are subject to change without prior notice.