

LTEG11

IP66 Latched Caixa da câmera com abertura lateral

Construção em alumínio com tampas plásticas, suporte interno com cabo gerenciado, tamanho interno utilizável (L x A x C): 85 mm x 85 mm x 300 mm



| Model | Illumination | Heater | Blower | Input Power |
|----------------|-----------------|--------|--------|------------------------------------|
| LTEG06-2-3 | | | + | 110 V AC |
| LTEG06-2-4 | | | + | 220 V AC |
| LTEG06-3-1 | | + | + | 12 V DC |
| LTEG06-3-2 | | + | + | 24 V AC |
| LTEG06-3-3 | | + | + | 110 V AC |
| LTEG06-3-4 | | + | + | 220 V AC |
| LTEG06-3-5 | | + | + | PoE |
| LTEG06-3-9 | | + | + | PoE (midspan only) ¹ |
| LTEG06-R30-0 | IR, 30 m, 60° | | | |
| LTEG06-R30-3-1 | IR, 30 m, 60° + | | + | 12 V DC |
| LTEG06-R30-3-2 | IR, 30 m, 60° + | | + | 24 V AC |
| LTEG06-R30-3-4 | IR, 30 m, 60° + | | + | 220 V AC |
| LTEG06-R30-3-5 | IR, 30 m, 60° + | | + | PoE |
| LTEG06-R50-0 | IR, 50 m, 15° | | | |
| LTEG06-R50-3-1 | IR, 50 m, 15° + | | + | 12 V DC |
| LTEG06-R50-3-2 | IR, 50 m, 15° + | | + | 24 V AC |
| LTEG06-R50-3-4 | IR, 50 m, 15° + | | + | 220 V AC |
| LTEG06-R50-3-5 | IR, 50 m, 15° + | | + | PoE |

Tech Specs

Features

- IP66, NEMA-4X enclosure rating
- Bundled adjustable sliding sunshield
- Designed for indoor and outdoor applications
- Input power: 12 V DC/24 V AC/110 V AC/220 V AC (available) or PoE (upgradable)
- Built-in heater and blower (optional)
- Built-in IR illuminator with distance up to 50 m (164.04 ft) (optional, input power: 12 V DC)
- Adjustable sliding camera tray
- Cable entry glands and mounting holes on bottom of housing
- Extruded aluminum body and sunshield; injection molded ABS plastic end caps
- Hinged side opening for easy installation and camera setup
- Side-mount link-lock latches for security
- Bundled internal cable managed bracket

Available Models

| Model | Illumination | Heater | Blower | Input Power |
|------------|--------------|--------|--------|-------------|
| LTEG06-0 | | | | |
| LTEG06-1-1 | | + | | 12 V DC |
| LTEG06-1-2 | | + | | 24 V AC |
| LTEG06-1-3 | | + | | 110 V AC |
| LTEG06-1-4 | | + | | 220 V AC |
| LTEG06-2-1 | | | + | 12 V DC |
| LTEG06-2-2 | | | + | 24 V AC |

| | |
|---|--|
| Model | LTEG06 |
| Type | Indoor/Outdoor, side opening, link-lock latches |
| Protection Rating | IP66, NEMA-4X enclosure rating |
| Material | Extruded aluminum body and sunshield; injection molded ABS plastic end caps |
| Finish | White polyester powder coat |
| Input Power | <ul style="list-style-type: none"> ▪ 12 V DC (LTEG06-1-1, LTEG06-2-1, LTEG06-3-1) ▪ 24 V AC (LTEG06-1-2, LTEG06-2-2, LTEG06-3-2) ▪ 110 V AC (LTEG06-1-3, LTEG06-2-3, LTEG06-3-3) ▪ 220 V AC (LTEG06-1-4, LTEG06-2-4, LTEG06-3-4) ▪ PoE (IEEE 802.3at Class 4 PoE Plus compliant) (LTEG06-3-5, LTEG06-R30-3-5, LTEG06-R50-3-5) ▪ PoE (48 V DC) (LTEG06-3-9)¹ |
| Power Consumption | <ul style="list-style-type: none"> ▪ Heater (24 V AC): 6 W (250 mA) ▪ Heater (220 V AC): 5.3 W (23 mA) ▪ Heater (12 V DC): 4.2 W (350 mA) ▪ Blower: 1.68 W (140 mA) ▪ IR LEDs: 4 W |
| Network Interface | <ul style="list-style-type: none"> ▪ RJ-45 × 2 (PoE input/data output) (LTEG06-3-5, LTEG06-R30-3-5, LTEG06-R50-3-5) ▪ RJ-45 × 2 (PoE input/PoE output) (LTEG06-3-9) |
| Dimensions (W × H × L) | 145 mm × mm 110 × mm 414 mm (5.71 in × 4.33 in × 16.30 in) |
| Window Viewing Area (W × H) | <ul style="list-style-type: none"> ▪ Outer dimensions: 75 mm × 75 mm (2.95 in × 2.95 in) ▪ Internal ring diameter: 50 mm (1.97 in) (LTEG06-R30-0, LTEG06-R50-0)³ |
| Window Thickness | 2 mm (0.08 in), tempered glass |
| Internal Usable Size (W × H × L)² | <ul style="list-style-type: none"> ▪ 85 mm × 85 mm × 300 mm (3.35 in × 3.35 in × 11.81 in) (LTEG06-0) ▪ 85 mm × 85 mm × 240 mm (3.35 in × 3.35 in × 9.45 in) (LTEG06-1-1, LTEG06-1-2, LTEG06-1-3, LTEG06-1-4) ▪ 85 mm × 85 mm × 210 mm (3.35 in × 3.35 in × 8.27 in) (LTEG06-2-1, LTEG06-2-2, LTEG06-2-3, LTEG06-2-4, LTEG06-3-1, LTEG06-3-2, LTEG06-3-3, LTEG06-3-4, LTEG06-3-5, LTEG06-3-9) |
| Heater Control | On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (LTEG06-1-1, LTEG06-1-2, LTEG06-1-3, LTEG06-1-4, LTEG06-3-1, LTEG06-3-2, LTEG06-3-3, LTEG06-3-4, LTEG06-3-5, LTEG06-3-9) |
| Blower Control | On at 40 °C ± 3 °C (104 °F ± 5 °F), off at 30 °C ± 3 °C (86 °F ± 5 °F) (LTEG06-2-1, LTEG06-2-2, LTEG06-2-3, LTEG06-2-4, LTEG06-3-1, LTEG06-3-2, LTEG06-3-3, LTEG06-3-4, LTEG06-3-5, LTEG06-3-9) |
| Operating Ambient Temperature | -40 to 60 °C (-40 °F to 140 °F) |
| Weight | <ul style="list-style-type: none"> ▪ 2.75 kg (6.06 lb) ▪ Max 3.1 kg (6.83 lb) (wall mount bracket included) ▪ Volumetric Weight: 4.04 kg (8.91 lb) (wall mount bracket included) |
| Certifications | CE, FCC, RoHS |
| Wavelength³ | 850 nm (LTEG06-R30-0, LTEG06-R50-0) |
| Illumination Distance³ | <ul style="list-style-type: none"> ▪ 30 m (98.42 ft) (LTEG06-R30-0) ▪ 50 m (164.04 ft) (LTEG06-R50-0) |
| Beam Angle³ | <ul style="list-style-type: none"> ▪ 60° (LTEG06-R30-0) ▪ 15° (LTEG06-R50-0) |
| LEDs³ | 24 pieces (LTEG06-R30-0, LTEG06-R50-0) |
| LED Lifetime³ | 20,000 hours (LTEG06-R30-0, LTEG06-R50-0) |
| Light On/Off³ | On when illumination is lower than 4 lux (LTEG06-R30-0, LTEG06-R50-0) |
| Related Products | LTMH02, LTMH05 |

LTEG06-R30-0 and LTEG06-R50-0 respectively.
 *Design and specifications are subject to change without prior notice.

1. It is only used for midsapn PoE switch or injector.
2. The internal usable size for LTEG06-R30-_- and LTEG06-R50-_- is the same as LTEV06-_-.
3. The spec for LTEG06-R30-_- and LTEG06-R50-_- is the same as