

LTES06

IP66 Caixa da câmera de aço inoxidável com abertura posterior



Model	LTES06
Size (W x H x L)	10.63 in <ul style="list-style-type: none"> 86 mm x 55 mm x 257 mm (3.39 in x 2.17 in x 10.12 in) (LTES06-R30-0) 108 mm x 250 mm (4.3 in x 9.8 in) (Ø x L) without internal bracket
Window Thickness	8 mm (0.31 in)
Window Viewing Area (Ø)	<ul style="list-style-type: none"> 70 mm (2.76 in) 30 mm (1.18 in) (LTES06-R30-0, LTES06-L-R30-0)
Weight	<ul style="list-style-type: none"> 6.5 kg (14.33 lb) 8.4 kg (18.52 lb) (wall mount bracket included) 7 kg (15.43 lb) (LTES06-R30-0, LTES06-L-R30-0) 8.9 kg (19.62 lb) (wall mount bracket included) (LTES06-R30-0, LTES06-L-R30-0)
Material	<ul style="list-style-type: none"> AISI 304 stainless steel (LTES06, LTES06-R30-0) AISI 316L stainless steel (LTES06-L, LTES06-L-R30-0)
Cable Outlet	G-3/4" x 2
Heater Control	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (optional)
Wavelength	850 nm (LTES06-R30-0, LTES06-L-R30-0)
Illumination Distance	30 m (98.43 ft) (LTES06-R30-0, LTES06-L-R30-0)
Beam Angle	60° (LTES06-R30-0, LTES06-L-R30-0)
LEDs	6 pieces (LTES06-R30-0, LTES06-L-R30-0)
LED Lifetime	> 25,000 hours (LTES06-R30-0, LTES06-L-R30-0)
Light On/Off	On when illumination is lower than 4 lux (LTES06-R30-0, LTES06-L-R30-0)
Related Products	-

*Design and specifications are subject to change without prior notice.

Features

- IP68, NEMA-6P enclosure rating
- Operating temperature range from -25 °C to 60 °C (-13 °F to 140 °F)
- AISI 304/316L stainless steel construction (available)
- Built-in IR illuminator with distance up to 30 m (98.42 ft) (optional, input power: 12 V DC)

Available Models

Model	Material	Illumination
LTES06-0	SS304	
LTES06-R30-0	SS304	IR, 30 m
LTES06-L-0	SS316L	
LTES06-L-R30-0	SS316L	IR, 30 m

Tech Specs

Model	LTES06
Type	Back opening
Atmospheric Pressure	80 kPa to 106 kPa
Operating Ambient Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Protection Rating	IP68, NEMA-6P enclosure rating
Input Power	220 V AC, 50 Hz (optional)
Dimensions (W x H x L)	140 mm x 140 mm x 348 mm (5.51 in x 5.51 in x 13.70 in)
Internal Usable	<ul style="list-style-type: none"> 86 mm x 55 mm x 270 mm (3.39 in x 2.17 in x