

LTEX08

Caixa Dome à Prova de Explosão (SS304)

24 cm (9.45 in), explosion proof dome housing, SS304



Model	LTEX08
Size (Ø x L)	
Window Viewing Area (Ø)	87 mm (3.43 in)
Weight	13 kg (28.66 lb)
Material	<ul style="list-style-type: none"> AISI 304 stainless steel (LTEX08) AISI 316L stainless steel (LTEX08-L)

*Design and specifications are subject to change without prior notice.

Features

- IP68, NEMA-6P enclosure rating
- Dome housing
- Operating temperature range from -30 °C to 70 °C (-22 °F to 158 °F)
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)

Available Models

Model	Material
LTEX08	AISI 304 stainless steel
LTEX08-L	AISI 316L stainless steel

Tech Specs

Model	LTEX08
Type	Dome housing
Atmospheric Pressure	80 kPa to 106 kPa
Operating Ambient Temperature	-30 °C to 70 °C (-22 °F to 158 °F)
Relative Humidity	5 % to 95 % noncondensing
Protection Rating	<ul style="list-style-type: none"> Ex d IIC T6 Gb explosion-proof marking IP68, NEMA-6P enclosure rating
Outlet Hole Thread	G-1/2"
Size	
Dimensions (Ø x L)	240 mm x 386 mm (9.45 in x 15.20 in)
Internal Usable	182 mm x 214 mm (7.17 in x 8.43 in)