

LTEX09

Caixa Dome à Prova de Explosão (SS304)

Ø 240 mm (9.5 in), explosion proof dome housing, SS304



Model	LTEX09
Size (Ø x H)	
Window Viewing Area (Ø)	-
Weight	11 kg (24.3 lb)
Material	<ul style="list-style-type: none"> AISI 304 stainless steel (LTEX09) AISI 316L stainless steel (LTEX09-L)

*Design and specifications are subject to change without prior notice.

Features

- IP68, NEMA-6P enclosure rating
- Dome housing
- Operating temperature range from -30 °C to 70 °C (-22 °F to 158 °F)
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)

Available Models

Model	Material
LTEX09	AISI 304 stainless steel
LTEX09-L	AISI 316L stainless steel

Tech Specs

Model	LTEX09
Type	Dome housing
Atmospheric Pressure	80 kPa to 106 kPa (11.6 PSI to 15.37 PSI)
Operating Ambient Temperature	-30 °C to 70 °C (-22 °F to 158 °F)
Relative Humidity	5 % to 95 % noncondensing
Protection Rating	<ul style="list-style-type: none"> Ex d IIC T6 Gb explosion-proof marking IP68, NEMA-6P enclosure rating
Outlet Hole Thread	G-1/2-inch
Size	
Dimensions (Ø x H)	240 mm x 357 mm (9.4 in x 14.1 in)
Internal Usable	176 mm x 195 mm (6.9 in x 7.7 in)