

LTMH15

Suporte Gerenciado por Cabo de Comprimento Ajustável

Comprimento ajustável de 305 mm a 465 mm (12,0 pol. a 18,3 pol.) e 617 mm a 1004 mm (24,3 pol. a 39,5 pol.) (opcional)



Model	LTMH15
Weight	<ul style="list-style-type: none"> • 460 g (1.0 lb) (LTMH15-P, LTMH15-S) • 633 g (1.4 lb) (LTMH15L-P, LTMH15L-S)
Related Products	-

*Design and specifications are subject to change without prior notice.

Features

- Designed for box camera, dome camera, camera housing mounting applications
- Aluminum construction
- Easy length adjustable
- Adjustable length up to 465 mm to 1004 mm (18.3 in to 39.5 in) (optional)
- Plate and screw head (available)

Available Models

Model	Adjustable Length	Head
LTMH15-P	305 mm to 465 mm (12.0 in to 18.3 in)	Plate
LTMH15-S	305 mm to 465 mm (12.0 in to 18.3 in)	Screw
LTMH15L-P	617 mm to 1004 mm (24.3 in to 39.5 in)	Plate
LTMH15L-S	617 mm to 1004 mm (24.3 in to 39.5 in)	Screw

Tech Specs

Model	LTMH15
Maximum Load	2 kg (4.4 lb)
Material	Aluminum
Finish	Sliver polyester powder coat
Dimensions (L x Ø)	<ul style="list-style-type: none"> • 305 mm to 465 mm x 120 mm (12.0 in to 18.3 in x 4.7 in) (LTMH15-P, LTMH15-S) • 617 mm to 1004 mm x 120 mm (24.3 in to 39.5 in x 4.7 in) (LTMH15L-P, LTMH15L-S)