

LTPM01

Unidade de Pan and Tilt Indoor

IP65, carga máxima de 7 kg (15,4 lb), construção em policarbonato e aço



Model	LTPM01
Pan Speed	5° per second
Pan Range	0° to 355° (auto/manual)
(Movement in Horizontal Plane)	
Tilt Speed	-
Tilt Range	-50° to 50° (manual)
(Movement in Vertical Plane)	
Operating Ambient Temperature	10 °C to 35 °C (50 °F to 95 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication Protocols	RS-485 (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4) Pelco D (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4)
Baud Rate	2,400/4,800/9,600 bps (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4)
Standard Setting	<ul style="list-style-type: none"> ▪ Available with BNC Cable (LTPM01-A-2, LTPM01-A-3, LTPM01-A-4) ▪ Available with network cable (100Mbps) (LTPM01-N-2, LTPM01-N-3, LTPM01-N-4)
Dimensions (W x H x L)	179 mm x 115 mm x 180 mm (7.0 in x 4.5 in x 7.1 in)
Weight	1.8 kg (3.97 lb)

*Design and specifications are subject to change without prior notice.

Features

- Polycarbonate and steel construction
- Maximum load 7 kg (15.4 lb)
- Designed for indoor applications
- Support analogue or network cameras (optional)
- Input power: 24 V AC/110 V AC/220 V AC (available)

Available Models

Model	Support	Input Power
LTPM01-A-2	Analogue	24 V AC
LTPM01-A-3	Analogue	110 V AC
LTPM01-A-4	Analogue	220 V AC
LTPM01-N-2	Network	24 V AC
LTPM01-N-3	Network	110 V AC
LTPM01-N-4	Network	220 V AC

Tech Specs

Model	LTPM01
Maximum Load	7 kg (15.4 lb)
Type	Indoor, top load
Protection Rating	IP65, NEMA-4 enclosure rating
Material	Polycarbonate and steel construction
Finish	Beige
Input Power	<ul style="list-style-type: none"> ▪ 24 V AC (LTPM01-A-2, LTPM01-N-2) ▪ 110 V AC (LTPM01-A-3, LTPM01-N-3) ▪ 220 V AC (LTPM01-A-4, LTPM01-N-4)
Power Consumption	8 W