

LTPM04

Unidade de Pan e Tilt Outdoor para cargas de até 15 kg (33,1 lb)

IP66, carga máxima de 15 kg (33,1 lb), Pan e Tilt ajustável de velocidade, construção em liga de alumínio



Model	LTPM04
Consumption	
Pan Speed	0.4° to 10° per second
Pan Range	0° to 360° continuous
(Movement in Horizontal Plane)	
Tilt Speed	0.4° to 2.5° per second
Tilt Range	• -60° to 10° for load 20 kg (44.1 lb) (factory setting)
(Movement in Vertical Plane)	
Accuracy	0.4°
Operating Ambient Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600 bps adjustable
Standard Setting	• Available with BNC Cable (LTPM04-A-6, LTPM04S-A-6) • Available with network cable (100Mbps) (LTPM04-N-6, LTPM04S-N-6)
OSD menu	Available
Heater	Optional
Dimensions (W x H x L)	• 301 mm x 217 mm x 184 mm (11.9 in x 8.5 in x 7.2 in) (LTPM04-A-6, LTPM04S-A-6) • 610 mm x 217 mm x 184 mm (24.0 in x 8.5 in x 7.2 in) (LTPM04-N-6, LTPM04S-N-6)
Weight	9.3 kg (20.5 lb)
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-6P enclosure rating
- Maximum load 15 kg (33.1 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)

Available Models

Model	Load	Support	Input Power
LTPM04-A-6	Top load	Analogue	24 V DC
LTPM04-N-6	Top load	Network	24 V DC
LTPM04S-A-6	Side load	Analogue	24 V DC
LTPM04S-N-6	Side load	Network	24 V DC

Tech Specs

Model	LTPM04
Maximum Load	15 kg (33.1 lb)
Type	Indoor/Outdoor, top load (LTPM04-A-6, LTPM04-N-6), side load (LTPM04S-A-6, LTPM04S-N-6)
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	24 V DC
Power	40 W