

LTPM05

Unidade de Pan and Tilt Outdoor

IP66, carga máxima de 15 kg (33,1 lb), pan tilt ajustável de velocidade, construção em liga de alumínio



Model	LTPM05
(Movement in Horizontal Plane)	
Tilt Range	-75° to 40° (-90° to 40° optional)
(Movement in Vertical Plane)	
Accuracy	0.225° ± 0.003°
Operating Ambient Temperature	-35 °C to 65 °C (-31 °F to 149 °F)
Relative Humidity	5 % to 95 % noncondensing
Auto Scan	Up to 5 lines, based on OSD function, configurable speed
Auto Cruise	Up to 8 groups, based on OSD function, configurable speed
Continuous Scan	8 line, configurable speed and angles
Angles Display	Support
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600/19,200 bps adjustable
Standard Setting	<ul style="list-style-type: none"> • Available with BNC Cable (LTPM05-A) • Available with network cable (100Mbps) (LTPM05-N)
OSD menu	Available
Preset	Up to 80
Lens Drivien	10 V/6 V software control and adaptive
Lens Interface	Support (pan and tilt preset configuration interface)
Surge Protection	GB/T17626.5-2008
Dimensions (W x H x L)	249 mm x 230 mm x 302 mm (9.80 in x 9.06 in x 11.89 in)
Weight	15 kg (33.1 lb)
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- Maximum load 15 kg (33.1 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Input power: 24 V AC
- Support analogue or network cameras (optional)

Available Models

Model	Support
LTPM05-A	Analogue
LTPM05-N	Network

Tech Specs

Model	LTPM05
Maximum Load	15 kg (33.1 lb)
Type	Indoor/Outdoor, top load
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	24 V AC ± 25 %
Power	max. 85 W (heater off), max. 95 W (heater on)
Consumption	
Pan Speed	0.01° to 60° per second
Tilt Speed	0.01° to 30° per second
Pan Range	0° to 360° continuous