

LTPM14

Unidade de Pan e Tilt Outdoor para cargas de até 80 kg (176,4 lb)

IP66, carga máxima de 80 kg (176,4 lb), pan e tilt ajustável de velocidade, construção em liga de alumínio



Model	Pan Speed	Tilt Speed	Support	Input Power
LTPM10H-A-6	1°/s to 40°/s	0.5°/s to 4.5°/s	Analogue	24 V DC
LTPM10H-A-7	1°/s to 40°/s	0.5°/s to 4.5°/s	Analogue	48 V DC
LTPM10H-N-6	1°/s to 40°/s	0.5°/s to 4.5°/s	Network	24 V DC
LTPM10H-N-7	1°/s to 40°/s	0.5°/s to 4.5°/s	Network	48 V DC

Tech Specs

Features

- IP66, NEMA-6P enclosure rating
- Maximum load 80 kg (176.4 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable and range selectable
- Support analogue or network cameras (optional)
- Input power: 24 V DC/ 48 V DC (optional)

Available Models

Model	Pan Speed	Tilt Speed	Support	Input Power
LTPM10-A-6	0.05°/s to 10.5°/s	0.05°/s to 4.5°/s	Analogue	24 V DC
LTPM10-A-7	0.05°/s to 10.5°/s	0.05°/s to 4.5°/s	Analogue	48 V DC
LTPM10-N-6	0.05°/s to 10.5°/s	0.05°/s to 4.5°/s	Network	24 V DC
LTPM10-N-7	0.05°/s to 10.5°/s	0.05°/s to 4.5°/s	Network	48 V DC
LTPM10M-A-6	0.15°/s to 30°/s	0.15°/s to 4.5°/s	Analogue	24 V DC
LTPM10M-A-7	0.15°/s to 30°/s	0.15°/s to 4.5°/s	Analogue	48 V DC
LTPM10M-N-6	0.15°/s to 30°/s	0.15°/s to 4.5°/s	Network	24 V DC
LTPM10M-N-7	0.15°/s to 30°/s	0.15°/s to 4.5°/s	Network	48 V DC

Model	LTPM10
Maximum Load	80 kg (176.4 lb)
Type	Indoor/Outdoor, top load
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	<ul style="list-style-type: none"> • 24 V DC (LTPM10-A-6, LTPM10-N-6, LTPM10M-A-6, LTPM10M-N-6, LTPM10H-A-6, LTPM10H-N-6) • 48 V DC (LTPM10-A-7, LTPM10-N-7, LTPM10M-A-7, LTPM10M-N-7, LTPM10H-A-7, LTPM10H-N-7)
Accuracy	± 0.05°
Pan Speed	<ul style="list-style-type: none"> • 0.05° to 10.5° per second (LTPM10-A-6, LTPM10-N-7, LTPM10M-A-6, LTPM10M-N-7) • 0.15° to 30° per second (LTPM10M-A-6, LTPM10M-N-7, LTPM10M-N-6, LTPM10M-N-7) • 1° to 40° per second (LTPM10H-A-6, LTPM10H-N-7, LTPM10H-N-6, LTPM10H-N-7)
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Tilt Speed	<ul style="list-style-type: none"> • 0.05° to 4.5° per second (LTPM10-A-6, LTPM10-N-7, LTPM10M-A-6, LTPM10M-N-7) • 0.15° to 4.5° per second (LTPM10M-A-6, LTPM10M-N-7, LTPM10M-N-6, LTPM10M-N-7) • 0.5° to 4.5° per second (LTPM10H-A-6, LTPM10H-N-7, LTPM10H-N-6, LTPM10H-N-7)
Tilt Range (Movement in Vertical Plane)	-60° to 60°
Power Consumption	<ul style="list-style-type: none"> • 20 W maximum (LTPM10-A-6, LTPM10-N-7, LTPM10M-A-6, LTPM10M-N-7) • 120 W maximum (LTPM10M-A-6, LTPM10M-N-7, LTPM10M-N-6, LTPM10M-N-7) • 50 W maximum (LTPM10H-A-6, LTPM10H-N-7, LTPM10H-N-6, LTPM10H-N-7)
Operating Ambient Temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Auto Scan	Up to 8 lines, based on OSD function, configurable speed
Auto Cruise	Up to 8 groups, based on OSD function, configurable speed
Keep Watch	Programmed a preset, an auto scan line or an auto cruise group, based on OSD function, dwell time counting down display
Helix Scan	8 line, configurable speed and angles
Continuous Scan	8 line, configurable speed and angles
Angles Display	Real-time on screen display/Response by query command
Communication Protocols	RS-485 Pelco-D
Baud Rate	1,200/2,400/4,800/9,600 bps adjustable
Standard Setting	<ul style="list-style-type: none"> • Available with BNC Cable (LTPM10-A-6, LTPM10-A-7, LTPM10M-A-6, LTPM10M-A-7, LTPM10H-A-6, LTPM10H-A-7) • Available with network cable (100Mbps) (LTPM10-N-6, LTPM10-N-7, LTPM10M-N-6, LTPM10M-N-7, LTPM10H-N-6, LTPM10H-N-7)
OSD menu	Available
Preset	128
Dimensions (W x H x L)	375 mm x 343 mm x 200 mm (14.8 in x 13.5 in x 7.9 in)
Weight	25 kg (55.1 lb)
Note	-

*Design and specifications are subject to change without prior notice.