

# LT SX04

## Unidade Pan Tilt à prova de explosão



<b>Model</b>	<b>LT SX04</b>
<b>Tilt Speed</b>	0.1° to 40° per second (fixed speed adjustable)
<b>Accuracy</b>	0.1°
<b>Atmospheric Pressure</b>	80 kPa to 106 kPa
<b>Operating Ambient Temperature</b>	-45 °C to 60 °C (-49 °F to 140 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Communication</b>	RS-485
<b>Protocols</b>	Pelco-D, Pelco-P
<b>Communication Speed</b>	1,200/2,400/4,800/9,600/19,200 bps adjustable
<b>Standard Setting</b>	<ul style="list-style-type: none"> <li>• Available with BNC cable (<b>LT SX04-A, LT SX04-A-L</b>)</li> <li>• RJ45 10/100 base (<b>LT SX04-N, LT SX04-N-L</b>)</li> </ul>
<b>Preset</b>	Up to 128
<b>Surge Protection</b>	-
<b>Internal Usable Size (Ø x L)</b>	132 mm x 260 mm (5.2 in x 10.2 in), dual housing
<b>Dimensions (W x H x L)</b>	430 mm x 430 mm x 320 mm (16.9 in x 16.9 in x 12.6 in)
<b>Weight</b>	33 kg (72.8 lb)
<b>Window Viewing Area (Ø)</b>	90 mm (3.5 in)
<b>Window Thickness</b>	10 mm (0.4 in)
<b>Number of Outlet Holes</b>	2 (internal diameter of 14 mm)
<b>Outlet Hole Thread</b>	G-3/4" x 1
<b>Size</b>	-
<b>Note</b>	-

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-4X enclosure rating
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)
- Support thermal camera and visible camera (optional)

### Available Models

Model	Support	Material
<b>LT SX04-A</b>	Analogue	SS304
<b>LT SX04-N</b>	Network	SS304
<b>LT SX04-A-L</b>	Analogue	SS316L
<b>LT SX04-N-L</b>	Network	SS316L

### Tech Specs

Model	LT SX04
<b>Protection Rating</b>	<ul style="list-style-type: none"> <li>• IP66, NEMA-4X enclosure rating</li> <li>• Ex d IIC T6 Gb explosion-proof marking</li> </ul>
<b>Material</b>	<ul style="list-style-type: none"> <li>• SS304 (<b>LT SX04-A, LT SX04-N</b>)</li> <li>• SS316L (<b>LT SX04-A-L, LT SX04-N-L</b>)</li> </ul>
<b>Finish</b>	Stainless steel original color
<b>Input Power</b>	220 V AC, 50/60 Hz
<b>Power Consumption</b>	100 W
<b>Pan Range (Movement in Horizontal Plane)</b>	0° to 360°
<b>Pan Speed</b>	0.1° to 40° per second (fixed speed adjustable)
<b>Tilt Range (Movement in Vertical Plane)</b>	-90° to 90°