

# LTAK01

## Control Panel



### Features

- Support Pelco-P/Pelco-D
- Joystick for accurate control
- LCD Display

### Tech Specs

|                                      |  |
|--------------------------------------|--|
| <b>Model</b>                         | LTAK01   |
| <b>Operating Ambient Temperature</b> | -10 °C to 50 °C (14 °F to 122 °F)                    |
| <b>Relative Humidity</b>             | 5 % to 95 % noncondensing                            |
| <b>Interface Connector</b>           | Can be connected to 32 RS485 nodes                   |
| <b>Communication Baud Rate</b>       | 1,200 bps, 2,400 bps, 4,800 bps, 9,600 bps           |
| <b>Communication Protocols</b>       | RS-485   |
| <b>Transmission Distance</b>         | Pelco-D, Pelco-P                                     |
| <b>Input Power</b>                   | 500 m (1640 ft)                                      |
| <b>Power Consumption</b>             | 12 V DC  |
| <b>Dimensions (L x W x H)</b>        | 6 W  |
| <b>Weight</b>                        | 330 mm x 145 mm x 100 mm (13.0 in x 5.7 in x 3.9 in) |
|                                      | 1.3 kg (2.9 lb)                                      |

\*Design and specifications are subject to change without prior notice.