

# LTAP07

Adaptor (24 V DC, 14.6 A)



## Features

- Up to 350 W
- Output voltage adjustable
- Built-in blower
- Operating Temperature up to 70 °C

## Tech Specs

<b>Model</b>	LTAP07
<b>Output Voltage</b>	24 V DC
<b>Output Current</b>	14.6 A max.
<b>Output Power</b>	350 W max.
<b>Output Voltage Adjustable Range</b>	21.6 V to 28.8 V
<b>Input</b>	90 V AC to 132 V AC / 180 V AC to 264 V AC by switch, 240 V DC to 370 V DC (switch on 230 V AC)
<b>Blower Control</b>	On at 50 °C ± 3 °C (122 °F ± 5 °F), off at 40 °C ± 3 °C (104 °F ± 5 °F)
<b>Dimensions (W × H × L)</b>	115 mm × 30 mm × 215 mm (4.5 in × 1.2 in × 8.5 in)
<b>Weight</b>	0.76 kg (1.7 lb)
<b>Operating Ambient Temperature</b>	-25 °C to 70 °C (-13 °F to 158 °F)
<b>Regulatory Compliance</b>	IEC/UL 62368-1, BSMI CNS14336-1, BS EN/EN60335-1, EAC TP TC 004, KC K60950-1 (for LRS-350-12/24 only), BIS IS13252(Part1): 2010/IEC 60950-1: 2005, AS/NZS62368.1 approved; Design refer to BS EN/EN62368-1

\*Design and specifications are subject to change without prior notice.