

LTCN15

Zoom Camera Module (8 MP, 30 fps, 30X)



Model	LTCN15
Audio Compression	G.711/AAC
Frame Rate	Max. 30 fps
WhiteBalance	Auto tracing white/Auto white/Manual
Analog Gain/Digital	1 to 30
Max Gain	
Exposure	Auto/Flat/Spot/Center
PTZ Control Protocol	40 types of control protocol including Pelco-D, Pelco-P, Visca
Network Protocol	Onvif, HTTP, HTTPS, IPv4, IPv6, RTSP, DDNS, RTP, TCP, UDP
Operating Ambient Temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Input Power	12 V DC
Power Consumption	Max. 5.5 W
Dimensions (L x W x H)	126 mm x 54 mm x 68 mm (5.0 in x 2.1 in x 2.7 in)
Weight	410 g (0.9 lb)

*Design and specifications are subject to change without prior notice.

Features

- 1/1.8-inch Sony CMOS sensor
- 30X optical zoom, 16X digital zoom
- Max 30 fps (3840 x 2160)
- H.265/H.264/MJPEG compression
- True WDR
- Autofocus
- ONVIF, PSIA compliant

Tech Specs

Model	LTCN15
Type	Network camera module
Image Sensor	1/1.8-inch Sony CMOS
Lens	f = 6 mm to 180 mm (30X), f/1.5 to f/4.3
Digital Zoom	16X
View of Angle	<ul style="list-style-type: none"> ▪ Horizontal: 65.2° (wide) to 2.4° (tele) ▪ Vertical: 39.5° (wide) to 1.3° (tele) ▪ Diagonal: 72.5° (wide) to 2.8° (tele)
Mini Focus Distance	1 m to 2 m
Effective Pixels	352 x 240 to 3840 x 2160
Minimum Illumination	<ul style="list-style-type: none"> ▪ Color: 0.01 lux at 1/15 sec, 50 IRE ▪ Day and Night: 0.001 lux at 1/15 sec, 50 IRE
Electronic Shutter Range	1/1 to 1/30,000 second
Wide Dynamic Range (WDR)	Level 1 to level 7
Digital Noise Reduction (DNR)	0 to 5, total 6 steps
Video Compression	H.265/H.264/MJPEG