

LTEV11

IP68 Side Opening Die-cast Aluminum Camera Housing

Die-cast aluminum construction, bundled internal cable managed bracket, internal usable size (W × H × L): 110 mm × 90 mm × 320 mm



Model	Insulation	Heater	Blower	Input Power
LTEV11-3-4		+	+	220 V AC
LTEV11-2-5			+	PoE
LTEV11-1D-U-1		Dual heaters		90 V AC to 230 V AC
LTEV11I-1D-U-1	+	Dual heaters		90 V AC to 230 V AC

Tech Specs

Features

- IP68, NEMA-6P enclosure rating
- Designed for indoor and outdoor applications
- Input power: 12 V DC/24 V AC/110 V AC/220 V AC/90 V AC to 230 V AC (available) or PoE (upgradable)
- Built-in heater, dual heater and blower (optional)
- Thermal insulation (upgradable)
- Adjustable sliding camera tray
- Cable entry glands and mounting holes on bottom of housing
- Die-cast aluminum construction
- High impact resistance
- Bundled internal cable managed bracket

Available Models

Model	Insulation	Heater	Blower	Input Power
LTEV11-0				
LTEV11-1-1		+		12 V DC
LTEV11-1-2		+		24 V AC
LTEV11-1-3		+		110 V AC
LTEV11-1-4		+		220 V AC
LTEV11-2-1			+	12 V DC
LTEV11-2-2			+	24 V AC
LTEV11-2-3			+	110 V AC
LTEV11-2-4			+	220 V AC
LTEV11-3-1		+	+	12 V DC
LTEV11-3-2		+	+	24 V AC
LTEV11-3-3		+	+	110 V AC

Model	LTEV11
Type	Indoor/Outdoor, side opening
Protection Rating	IP68, NEMA-6P enclosure rating
Material	Die-cast aluminum
Finish	White polyester powder coat
Input Power	<ul style="list-style-type: none"> 12 V DC (LTEV11-1-1, LTEV11-2-1, LTEV11-3-1) 24 V AC (LTEV11-1-2, LTEV11-2-2, LTEV11-3-2) 110 V AC (LTEV11-1-3, LTEV11-2-3, LTEV11-3-3) 220 V AC (LTEV11-1-4, LTEV11-2-4, LTEV11-3-4) PoE (IEEE 802.3at Class 4 PoE Plus compliant) (LTEV11-2-5) 90 V AC to 230 V AC (LTEV11-1D-U-1, LTEV11-1D-U-1)
Output Power	12 V DC, 3 A (LTEV11-1D-U-1, LTEV11-1D-U-1)
Power Consumption	<ul style="list-style-type: none"> Heater (12 V DC/24 V AC/110 V AC/ 220 V AC): 30 W Dual heater (220 V AC): max. 60 W (LTEV11-1D-U-1, LTEV11-1D-U-1) Blower: 2 W (167 mA)
Network Interface	RJ-45 × 2 (PoE input/data output) (LTEV11-2-5)
Dimensions (W × H × L)	140 mm × 130 mm × 405 mm (5.5 in × 5.1 in × 15.9 in)
Window Viewing Area (W × H)	80 mm × 80 mm (3.1 in × 3.1 in)
Window Thickness	3 mm (0.12 in), tempered glass
Internal Usable Size (W × H × L)	<ul style="list-style-type: none"> 110 mm × 90 mm × 320 mm (4.3 in × 3.5 in × 12.6 in) 110 mm × 90 mm × 230 mm (4.3 in × 3.5 in × 9.1 in) (LTEV11-1D-U-1, LTEV11-1D-U-1)
Heater Control	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (LTEV11-1-1, LTEV11-1-2, LTEV11-1-3, LTEV11-1-4, LTEV11-3-1, LTEV11-3-2, LTEV11-3-3, LTEV11-3-4, LTEV11-1D-U-1, LTEV11-1D-U-1)
Blower Control	On at 35 °C ± 3 °C (95 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (LTEV11-2-1, LTEV11-2-2, LTEV11-3-2, LTEV11-2-4, LTEV11-3-1, LTEV11-3-2, LTEV11-3-3, LTEV11-3-4, LTEV11-2-5)
Operating Ambient Temperature	<ul style="list-style-type: none"> -40 °C to 60 °C (-40 °F to 140 °F) -40 °C to 40 °C (-40 °F to 104 °F) (LTEV11-1D-U-1) -55 °C to 40 °C (-67 °F to 104 °F) (LTEV11-1D-U-1)
Weight	<ul style="list-style-type: none"> 3.1 kg (6.8 lb) Max. 3.8 kg (8.4 lb) (wall mount bracket included) 3.45 kg (7.6 lb) (LTEV11-1D-U-1, LTEV11-1D-U-1) Max. 4.15 kg (9.1 lb) (wall mount bracket included) (LTEV11-1D-U-1, LTEV11-1D-U-1)
Certifications	CE, FCC, RoHS
Related Products	-

1. It is only used for midsapn PoE switch or injector.

*Design and specifications are subject to change without prior notice.