

# LTEX15

## IP68 Explosion Proof Camera Housing with Heat Sink (SS304)

|                         |   |
|-------------------------|---|
| <b>Model</b>            | <b>LTEX15</b>   |
| <b>Area (Ø)</b>         |   |
| <b>Window Thickness</b> | -   |
| <b>Weight</b>           | 9.5 kg (20.9 lb) (without wall mount bracket)   |
| <b>Material</b>         | <ul style="list-style-type: none"> <li>• AISI 304 stainless steel (<b>LTEX15</b>)</li> <li>• AISI 316L stainless steel (<b>LTEX15-L</b>)</li> </ul> |
| <b>Heater Control</b>   | -   |
| <b>Related Products</b> | -   |

\*Design and specifications are subject to change without prior notice.



### Features

- IP68, NEMA-6P enclosure rating
- Built-in automatic air-conditioning
- Operating temperature range from -40 °C to 65 °C (-49 °F to 149 °F)
- Ex d IIB T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)

### Available Models

| Model           | Material                  |
|-----------------|---------------------------|
| <b>LTEX15</b>   | AISI 304 stainless steel  |
| <b>LTEX15-L</b> | AISI 316L stainless steel |

### Tech Specs

| Model                                | LTEX15   |
|--------------------------------------|--|
| <b>Type</b>                          | Back opening   |
| <b>Atmospheric Pressure</b>          | 86 kPa to 106 kPa  |
| <b>Operating Ambient Temperature</b> | -40 °C to 65 °C (-49 °F to 149 °F)   |
| <b>Relative Humidity</b>             | 5 % to 95 % noncondensing  |
| <b>Protection Rating</b>             | <ul style="list-style-type: none"> <li>• Ex d IIB T6 Gb explosion-proof marking</li> <li>• IP68, NEMA-6P enclosure rating</li> </ul> |
| <b>Input Power</b>                   | 12 V DC/24 V AC  |
| <b>Dimensions (Ø x L)</b>            | 160 mm x 340 mm (6.3 in x 13.4 in)   |
| <b>Internal Usable Size (Ø x L)</b>  | 120 mm x 260 mm (4.7 in x 10.2 in)   |
| <b>Window Viewing</b>                | 67 mm (2.6 in)   |