

LTPM03

Outdoor Pan and Tilt Unit for Loads up to 6 kg (13.2 lb)

IP66, maximum load of 6 kg (13.2 lb), speed adjustable pan and tilt, aluminum alloy construction



Model	LTPM03
Tilt Speed	0.2° to 7.5° per second
Pan Range	<ul style="list-style-type: none"> • 0° to 360° continuous (LTPM03) • Limit pan range (selectable) (LTPM03-L)
(Movement in Horizontal Plane)	
Tilt Range	-60° to 30°
(Movement in Vertical Plane)	
Accuracy	±0.1°
Operating Ambient Temperature	-10 °C to 50 °C (-14 °F to 122 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600 bps adjustable
Standard Setting	Available with BNC or network cable (selectable)
OSD menu	Available
Preset	Up to 130
Surge Protection	GB/T17626.5-2008
Dimensions (W × H × L)	165 mm × 263 mm × 146 mm (6.5 in × 10.4 in × 5.8 in)
Weight	6.5 kg (14.3 lb)
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- Maximum load 6 kg (13.2 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Input power: 24 V DC
- Support analogue or network cameras (optional)

Available Models

Model	Pan Range
LTPM03	0° to 360° continuous
LTPM03-L	Limit pan range (selectable)

Tech Specs

Model	LTPM03
Maximum Load	6 kg (13.2 lb)
Type	Indoor/Outdoor, top load
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	24 V DC
Power	30 W
Consumption	
Pan Speed	0.2° to 15° per second