

LTPM15

Outdoor Pan and Tilt Unit for Loads up to 30 kg (66.1 lb)

IP66, maximum load of 30 kg (66.1 lb), speed adjustable pan and tilt, aluminum alloy construction



Model	LTPM15
Power protection	TVS 8000V lightning proof, surge proof, in line with GB/T17626.5 Level
Accuracy	± 0.01 °
Pan Speed	0.22° to 30° per second
Pan Range	0° to 360° continuous
(Movement in Horizontal Plane)	
Tilt Speed	0.3° to 13° per second
Tilt Range	-55° to 60°
(Movement in Vertical Plane)	
Power	100 W maximum
Consumption	
Operating Ambient Temperature	-40 °C to 65 °C (-40 °F to 149 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485/RS-422
Protocols	Pelco-D
Baud Rate	9,600 bps adjustable
Standard Setting	<ul style="list-style-type: none"> Available with BNC Cable (LTPM15-A-6, LTPM15-A-7) Available with network cable (100Mbps) (LTPM15-N-6, LTPM15-N-7)
OSD menu	Available
Preset	128
Dimensions (W × H × L)	215 mm × 343 mm × 387 mm (8.5 in × 13.5 in × 15.2 in)
Weight	21 kg (46.3 lb)
Note	-

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-6P enclosure rating
- Maximum load 30 kg (66.1 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)
- Input power: 24 V DC/ 48 V DC (optional)

Available Models

Model	Support	Input Power
LTPM15-A-6	Analogue	24 V DC
LTPM15-A-7	Analogue	48 V DC
LTPM15-N-6	Network	24 V DC
LTPM15-N-7	Network	48 V DC

Tech Specs

Model	LTPM15
Maximum Load	30 kg (66.1 lb)
Type	Indoor/Outdoor, top load
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Aluminum alloy
Finish	Beige
Input Power	<ul style="list-style-type: none"> 24 V DC (LTPM15-A-6, LTPM15-N-6) 48 V DC (LTPM15-A-7, LTPM15-N-7)