

# LTSU07

## Outdoor Pan and Tilt Unit



<b>Model</b>	<b>LTSU07</b>
<b>Baud Rate</b>	2,400/4,800/9,600/19,200 bps adjustable
<b>Standard Setting</b>	Available with BNC cable and network cable
<b>Surge Protection</b>	Built-in lightning and surge protection
<b>Internal Usable Size (W x L x H)</b>	140 mm x 125 mm x 400 mm (5.5 in x 4.9 in x 15.7 in) (both the same)
<b>Dimensions (W x L x H)</b>	235 mm x 740 mm x 492 mm (9.3 in x 29.1 in x 19.4 in)
<b>Weight</b>	25.5 kg (56.2 lb)
<b>Wavelength</b>	-
<b>Illumination</b>	-
<b>Distance</b>	-
<b>Beam angle</b>	-

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-4X enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Wiper (optional)
- Support analogue or network cameras (optional)

### Tech Specs

<b>Model</b>	LTSU07
<b>Type</b>	Indoor/Outdoor
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	High-strength aluminum
<b>Finish</b>	Beige
<b>Input Power</b>	24 V AC/24 V DC
<b>Power</b>	85 W (heater: 10 W), standby max. 15 W
<b>Consumption</b>	
<b>Pan Speed</b>	0.1° to 60° per second
<b>Pan Range (Movement in Horizontal Plane)</b>	0° to 360° continuous
<b>Tilt Speed</b>	0.1° to 30° per second
<b>Tilt Range (Movement in Vertical Plane)</b>	-75° to 40°
<b>Accuracy</b>	0.0225° ± 0.003°
<b>Operating Ambient Temperature</b>	-35 °C to 65 °C (-31 °F to 149 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Communication</b>	RS-485
<b>Protocols</b>	Pelco-D, Pelco-P