

LTSU09

HD Thermal Heavy PTZ System

Model	LTSU09
Size (W x H x L)	
Dimensions (W x H x L)	333 mm x 633 mm x 680 mm (13.1 in x 24.9 in x 26.8 in)
Weight	55 kg (121.3 lb)

*Design and specifications are subject to change without prior notice.



Features

- IP66, NEMA-6P enclosure rating
- Camera optional

Tech Specs

Model	LTSU09
Type	Indoor/Outdoor
Protection Rating	IP66, NEMA-4X enclosure rating
Material	High-strength aluminum
Finish	White
Input Power	24 V DC/24 V AC
Power	100 W maximum
Consumption	
Pan Speed	0.01° to 100° per second adjustable
Pan Range	0° to 360° continuous
(Movement in Horizontal Plane)	
Tilt Speed	0.01° to 60° per second adjustable
Tilt Range	-70° to 40°
(Movement in Vertical Plane)	
Accuracy	± 0.01°
Operating Ambient Temperature	-35 °C to 60 °C (-31 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600 bps adjustable
Standard Setting	Available with BNC cable and network cable
Surge Protection	Built-in lightning and surge protection
Internal Usable	200 mm x 180 mm x 500 mm (7.9 in x 7.1 in x 19.7 in)