

# LTAK12 Control Panel

Model	LTAK12
Weight	0.5 kg (1.1 lb)

\*Design and specifications are subject to change without prior notice.



## Features

- RS-485/USB 2.0 (optional)
- Joystick for accurate control
- LCD Display

## Available Models

Model	Communication
LTAK12	RS-485
LTAK12-U	USB

## Tech Specs

Model	LTAK12
Joystick	4D
Control Address	0 to 255
Operating Ambient Temperature	0 °C to 50 °C (32 °F to 131 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication	<ul style="list-style-type: none"> <li>• RS-485 (LTAK12)</li> <li>• USB 2.0 (LTAK12-U)</li> </ul>
Communication Baud Rate	1,200 bps, 2,400 bps, 4,800 bps, 9,600 bps (LTAK12)
Protocols	<ul style="list-style-type: none"> <li>• Pelco-D, Pelco-P, Dahua, Hik (LTAK12)</li> <li>• Hid (LTAK12-U)</li> </ul>
Input Power	<ul style="list-style-type: none"> <li>• 12 V DC (LTAK12)</li> <li>• 5 V DC ( LTAK12-U)</li> </ul>
Power Consumption	<ul style="list-style-type: none"> <li>• 0.6 W maximum (LTAK12)</li> <li>• 0.5 W maximum (LTAK12-U)</li> </ul>
Dimensions (W × H × L)	158 mm × 107 mm × 150 mm (6.2 in × 4.2 in × 5.9 in)