

# LTES14

## IP68 Spark-proof Air-conditioning Camera Housing



### Features

- IP68, NEMA-6P enclosure rating
- Built-in automatic air-conditioning
- Operating temperature range from -40 °C to 65 °C (-49 °F to 149 °F)
- Ex nR IIC T4 Gc spark-proof marking
- Aluminum construction

### Tech Specs

<b>Model</b>	<b>LTES14</b>
Atmospheric Pressure	86 kPa to 106 kPa
Operating Ambient Temperature	-40 °C to 65 °C (-49 °F to 149 °F)
Relative Humidity	5 % to 95 % noncondensing
Protection Rating	<ul style="list-style-type: none"> <li>• Ex nR IIC T4 Gc spark-proof marking</li> <li>• IP68, NEMA-6P enclosure rating</li> </ul>
Input Power	12 V DC/24 V DC
Outlet Hole	G-3/4" thread
Dimensions (Ø × L)	110 mm × 298 mm (4.33 in × 11.73 in)
Internal Usable Size (Ø × L)	101 mm × 240 mm (3.98 in × 9.45 in)
Window Viewing Area (Ø)	-
Weight	1.8 kg (8.82 lb)
Material	Aluminum

\*Design and specifications are subject to change without prior notice.