

LTEV13

IP66 Side Opening Die-cast Aluminum Camera Housing

Die-cast aluminum construction, bundled wall mount bracket, internal usable size (W × H × L): 120 mm × 90 mm × 320 mm



Model	Wiper	Heater	Blower	Input Power
LTEV13-3-4		+	+	220 V AC
LTEV13-2-5			+	PoE
LTEV13-W-0	+			
LTEV13-W-1-1	+	+		12 V DC
LTEV13-W-1-2	+	+		24 V AC
LTEV13-W-1-3	+	+		110 V AC
LTEV13-W-1-4	+	+		220 V AC
LTEV13-W-2-1	+		+	12 V DC
LTEV13-W-2-2	+		+	24 V AC
LTEV13-W-2-3	+		+	110 V AC
LTEV13-W-2-4	+		+	220 V AC
LTEV13-W-3-1	+	+	+	12 V DC
LTEV13-W-3-2	+	+	+	24 V AC
LTEV13-W-3-3	+	+	+	110 V AC
LTEV13-W-3-4	+	+	+	220 V AC
LTEV13-W-2-5	+		+	PoE

Tech Specs

Features

- IP66, NEMA-4P enclosure rating
- Designed for indoor and outdoor applications
- Input power: 12 V DC/24 V AC/110 V AC/220 V AC (available) or PoE (upgradable)
- Built-in heater and blower (optional)
- Built-in wiper (optional)
- Adjustable sliding camera tray
- Cable entry glands and mounting holes on bottom of housing
- Die-cast aluminum construction
- High impact resistance
- Bundled wall mount bracket

Available Models

Model	Wiper	Heater	Blower	Input Power
LTEV13-0				
LTEV13-1-1		+		12 V DC
LTEV13-1-2		+		24 V AC
LTEV13-1-3		+		110 V AC
LTEV13-1-4		+		220 V AC
LTEV13-2-1			+	12 V DC
LTEV13-2-2			+	24 V AC
LTEV13-2-3			+	110 V AC
LTEV13-2-4			+	220 V AC
LTEV13-3-1		+	+	12 V DC
LTEV13-3-2		+	+	24 V AC
LTEV13-3-3		+	+	110 V AC

Model	LTEV13
Type	Indoor/Outdoor, side opening
Protection Rating	IP66, NEMA-4P enclosure rating
Material	Die-cast aluminum
Finish	White polyester powder coat
Input Power	<ul style="list-style-type: none"> • 12 V DC (LTEV13-1-1, LTEV13-2-1, LTEV13-3-1, LTEV13-W-1-1, LTEV13-W-2-1, LTEV13-W-3-1) • 24 V AC (LTEV13-1-2, LTEV13-2-2, LTEV13-3-2, LTEV13-W-1-2, LTEV13-W-2-2, LTEV13-W-3-2) • 110 V AC (LTEV13-1-3, LTEV13-2-3, LTEV13-3-3, LTEV13-W-1-3, LTEV13-W-2-3, LTEV13-W-3-3) • 220 V AC (LTEV13-1-4, LTEV13-2-4, LTEV13-3-4, LTEV13-W-1-4, LTEV13-W-2-4, LTEV13-W-3-4) • PoE (IEEE 802.3at Class 4 PoE Plus compliant) (LTEV13-2-5, LTEV13-W-2-5)
Power Consumption	<ul style="list-style-type: none"> • Heater (12 V DC/24 V AC/110 V AC/ 220 V AC): 30 W • Blower: 2 W (167 mA)
Network Interface	RJ-45 × 2 (PoE input/data output) (LTEV13-2-5, LTEV13-W-2-5)
Dimensions (W × H × L)	170 mm × 127.5 mm × 500 mm (6.7 in × 5.0 in × 19.7 in)
Window Viewing Area (W × H)	94 mm × 70 mm (3.7 in × 2.8 in)
Window Thickness	3 mm (0.12 in), tempered glass
Internal Usable Size (W × H × L)	120 mm × 90 mm × 320 mm (4.7 in × 3.5 in × 12.6 in)
Heater Control	On at 0 °C ± 3 °C (32 °F ± 5 °F), off at 5 °C ± 3 °C (41 °F ± 5 °F) (LTEV13-1-1, LTEV13-1-2, LTEV13-1-3, LTEV13-1-4, LTEV13-3-1, LTEV13-3-2, LTEV13-3-3, LTEV13-3-4, LTEV13-W-1-1, LTEV13-W-1-2, LTEV13-W-1-3, LTEV13-W-1-4, LTEV13-W-3-1, LTEV13-W-3-2, LTEV13-W-3-3, LTEV13-W-3-4)
Blower Control	On at 45 °C ± 3 °C (113 °F ± 5 °F), off at 35 °C ± 3 °C (95 °F ± 5 °F) (LTEV13-2-1, LTEV13-2-2, LTEV13-3-2, LTEV13-2-4, LTEV13-3-1, LTEV13-3-2, LTEV13-3-3, LTEV13-3-4, LTEV13-2-5, LTEV13-W-2-1, LTEV13-W-2-2, LTEV13-W-3-2, LTEV13-W-2-4, LTEV13-W-3-1, LTEV13-W-3-2, LTEV13-W-3-3, LTEV13-W-3-4, LTEV13-W-2-5)
Operating Ambient Temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Weight	<ul style="list-style-type: none"> • 3.1 kg (6.8 lb) • Max. 3.8 kg (8.4 lb) (wall mount bracket included)
Certifications	CE, FCC, RoHS
Related Products	-

*Design and specifications are subject to change without prior notice.