

# LTEV15

## IP66 Line Scan Camera Housing



<b>Model</b>	LTEV15
<b>Area (W × H)</b>	
<b>Window Thickness</b>	3 mm (0.12 in), tempered glass
<b>Internal Usable Size (W × H × L)</b>	160 mm × 136 mm × 357 mm (6.3 in × 5.7 in × 14.1 in) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)
<b>Heater Control</b>	On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)
<b>Blower Control</b>	On at 40 °C ± 3 °C (104 °F ± 5 °F), off at 30 °C ± 3 °C (86 °F ± 5 °F) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)
<b>Operating Ambient Temperature</b>	-40 °C to 60 °C (-40 °F to 140 °F) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)
<b>Weight</b>	<ul style="list-style-type: none"> <li>• 4 kg (8.8 lb) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)</li> <li>• Max. 4.7 kg (10.4 lb) (wall mount bracket included) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)</li> </ul>
<b>Certifications</b>	CE, FCC, RoHS
<b>Related Products</b>	-

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-4X enclosure rating
- Designed for indoor and outdoor applications
- Included sunshield
- Input power: 12 V DC/24 V AC/220 V AC (available)
- Adjustable sliding camera tray

### Available Models

Model	Heater	Blower	Input Power
LTEV15-3-1	+	+	12 V DC
LTEV15-3-2	+	+	24 V AC
LTEV15-3-4	+	+	220 V AC

### Tech Specs

<b>Model</b>	LTEV15
<b>Type</b>	Indoor/Outdoor, side opening, for lin scan camera
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	Aluminum
<b>Finish</b>	White polyester powder coat
<b>Input Power</b>	<ul style="list-style-type: none"> <li>• 12 V DC (LTEV15-3-1)</li> <li>• 24 V AC (LTEV15-3-2)</li> <li>• 220 V AC (LTEV15-3-4)</li> </ul>
<b>Output Power</b>	-
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Heater (12 V DC): 4.2 W (350 mA) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)</li> <li>• Blower: 1.68 W (140 mA)</li> </ul>
<b>Dimensions (W × H × L)</b>	162 mm × 166 mm × 486.5 mm (6.4 in × 6.5 in × 19.2 in) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)
<b>Window Viewing</b>	-