

# LTPM11

## Outdoor Pan and Tilt Unit for Loads up to 9 kg (19.8 lb)

IP66, maximum load of 9 kg (19.8 lb), speed adjustable pan and tilt, aluminum alloy construction



Model	LTPM11
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600 bps adjustable
Standard Setting	Available with BNC cable and network cable
Dimensions (W × H × L)	223 mm × 350 mm × 250 mm (8.8 in × 13.8 in × 9.8 in)
Packing Dimensions (W × H × L)	340 mm × 310 mm × 820 mm (13.4 in × 12.2 in × 32.3 in)
Weight	10 kg (22.0 lb)

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-4X enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)

### Tech Specs

Model	LTPM11
Maximum Load	9 kg (19.8 lb)
Type	Indoor/Outdoor
Protection Rating	IP66, NEMA-4X enclosure rating
Material	High-strength aluminum
Finish	Beige
Input Power	24 V DC/24 V AC
Power Consumption	60 W (heater: 25 W), standby max. 15 W
Pan Speed	0.1° to 100° per second
Pan Range	0° to 360° continuous
(Movement in Horizontal Plane)	
Tilt Speed	0.1° to 100° per second
Tilt Range	-90° to 40°
(Movement in Vertical Plane)	
Accuracy	0.1°
Operating Ambient Temperature	-30 °C to 60 °C (-22 °F to 140 °F)