

*Design and specifications are subject to change without prior notice.

LTAK05

B?ng ?i?u khi?n hi?n th? 8inch



Features

- Support Pelco-P/Pelco-D
- Support HD-SDI input
- Support ABS, VGA input
- Joystick for accurate control
- 8-inch TFT LCD Display
- Alarm function and shortcut key available

Tech Specs

Model	LTAK05
Display	8-inch TFT LCD
Video Input	Composite video (NTSC/PAL), VGA, HD-SDI
Operating Ambient Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Relative Humidity	5 % to 95 % noncondensing
Interface Connector	6 pins interface, DB 9 pins female outlet, RJ45
Communication Baud Rate	2,400 bps, 4,800 bps, 9,600 bps, 19,200 bps
Communication Protocols	RS-485, RS-422, RS-232, USB2.0
Transmission Distance	Pelco-D, Pelco-P, Visca, Dahua, Kaikan
Battery	1200 m (3937 ft)
Input Power	Ni-MH 700 mAh
Power Consumption	9 V DC to 12 V DC
Dimensions (L x W x H)	4.2 W
Weight	290 mm x 181 mm x 95 mm (11.4 in x 7.1 in x 3.7 in)
	1.6 kg (3.5 lb)