

# LTEG07

## V? camera ch?t m? tr?n, c?a s? ??i, IP66

K?t c?u b?ng nhôm v?i n?p nh?a cu?i, gi? ?? qu?n lý b?ng cáp n?i b? ?i kèm, kích th??c có th? s? d?ng bên trong (W x H x L): 108 mm x 130 mm x 350 mm (m?t ??n)

Model	Wiper	Heater	Blower	Input Power
LTEG07-W-1-4	+	+		220 V AC
LTEG07-W-2-2	+		+	24 V AC
LTEG07-W-2-4	+		+	220 V AC
LTEG07-W-3-2	+	+	+	24 V AC
LTEG07-W-3-4	+	+	+	220 V AC

### Tech Specs



### Features

- IP66, NEMA-4X enclosure rating
- Designed for indoor and outdoor applications
- Input power: 24 V AC/220 V AC (available)
- Built-in heater, blower, wiper and sunshield (optional)
- Adjustable sliding camera tray
- Cable entry glands and mounting holes on bottom of housing
- Hinged top opening for easy installation and camera setup
- Side-mount link-lock latches for security
- Two different size optional

### Available Models

Model	Dimention
LTEG07	Normal size
LTEG07L	Large size

\*The different sizes in above table have the following models available.

Model	Wiper	Heater	Blower	Input Power
LTEG07-0				
LTEG07-1-2		+		24 V AC
LTEG07-1-4		+		220 V AC
LTEG07-2-2			+	24 V AC
LTEG07-2-4			+	220 V AC
LTEG07-3-2		+	+	24 V AC
LTEG07-3-4		+	+	220 V AC
LTEG07-W-0-2	+			24 V AC
LTEG07-W-0-4	+			220 V AC
LTEG07-W-1-2	+	+		24 V AC

<b>Model</b>	LTEG07
<b>Type</b>	Indoor/Outdoor, top opening, link-lock latches
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	Extruded aluminum body and sunshield
<b>Finish</b>	White polyester powder coat
<b>Input Power</b>	<ul style="list-style-type: none"> <li>• 24 V AC (LTEG07-1-2, LTEG07-2-2, LTEG07-3-2, LTEG07-W-0-2, LTEG07-W-1-2, LTEG07-W-2-2, LTEG07-W-3-2)</li> <li>• 220 V AC (LTEG07-1-4, LTEG07-2-4, LTEG07-3-4, LTEG07-W-0-4, LTEG07-W-1-4, LTEG07-W-2-4, LTEG07-W-3-4)</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Heater: 10 W</li> <li>• Blower: 2 W</li> <li>• Wiper: 5 W</li> </ul>
<b>Network Interface</b>	-
<b>Dimensions (W x H x L)<sup>1</sup></b>	<ul style="list-style-type: none"> <li>• LTEG07-0, LTEG07-W-1: 366 mm x 185 mm x 524 mm (14.4 in x 7.3 in x 20.6 in)</li> <li>• LTEG07L-0, LTEG07L-W-1: 366 mm x 185 mm x 600 mm (14.4 in x 7.3 in x 23.6 in)</li> </ul>
<b>Window Viewing Area (W x H)</b>	100 mm x 90 mm (3.9 in x .55 in)
<b>Window Thickness</b>	2 mm (0.08 in), tempered glass
<b>Internal Usable Size (W x H x L)<sup>1</sup></b>	<ul style="list-style-type: none"> <li>• LTEG07-0, LTEG07-W-1: 108 mm x 130 mm x 350 mm (4.3 in x 5.1 in x 13.8 in), single side</li> <li>• LTEG07L-0, LTEG07L-W-1: 108 mm x 130 mm x 426 mm (4.3 in x 5.1 in x 16.8 in), single side</li> </ul>
<b>Heater Control</b>	On at 8 °C ± 5 °C (46 °F ± 18 °F), off at 20 °C ± 3 °C (68 °F ± 11 °F) (LTEG07-1-2, LTEG07-1-4, LTEG07-3-2, LTEG07-3-4, LTEG07-W-1-2, LTEG07-W-1-4, LTEG07-W-3-2, LTEG07-W-3-4)
<b>Blower Control</b>	On at 38 °C ± 5 °C (100 °F ± 18 °F), off at 20 °C ± 3 °C (68 °F ± 11 °F) (LTEG07-2-2, LTEG07-2-4, LTEG07-3-2, LTEG07-3-4, LTEG07-W-2-2, LTEG07-W-2-4, LTEG07-W-3-2, LTEG07-W-3-4)
<b>Operating Ambient Temperature</b>	-35 to 65 °C (-95 °F to 149 °F)
<b>Weight<sup>1</sup></b>	<ul style="list-style-type: none"> <li>• LTEG07-0: 6.8 kg (15.0 lb)</li> <li>• LTEG07L-0: 7.8 kg (17.2 lb)</li> <li>• Wiper: 0.3 kg (0.7 lb)</li> </ul>
<b>Certifications</b>	CE, FCC, RoHS
<b>Related Products</b>	-

1. The specs for LTEG07-\_- and LTEG07L-\_- are the same as LTEG07-0 and LTEG07L-0 respectively.

\*Design and specifications are subject to change without prior notice.