

LTEG23

V? hình ??n IP66 cho mô?-?un camera

Model	LTEG23
Internal Usable Size (W x H x L)	48 mm x 155 mm (2.2 in x 1.9 in x 6.1 in) (LTEG23) • 40 mm x 34 mm x 97 mm (1.6 in x 1.5 in x 3.8 in) (LTEG23S)
Related Products	-
Weight	• 0.98 kg (2.2 lb) (LTEG23) • 0.4 kg (0.9 lb) (LTEG23S)
Certifications	RoHS

*Design and specifications are subject to change without prior notice.



Features

- IP66, NEMA-4X enclosure rating
- Designed for indoor and outdoor applications
- Die-cast aluminum construction
- Compact size (selectable)

Available Models

Model	Dimension
LTEG23	93 mm x 80.6 mm x 290 mm (3.7 in x 3.2 in x 11.4 in)
LTEG23S	68 mm x 64.7 mm x 208.7 mm (2.7 in x 2.5 in x 8.2 in)

Tech Specs

Model	LTEG23
Type	Indoor/Outdoor, bullet type
Protection Rating	IP66, NEMA-4X enclosure rating
Material	Die-cast aluminum
Finish	White polyester powder coat
Input Power	-
Dimensions (W x H x L)	• 93 mm x 80.6 mm x 290 mm (3.7 in x 3.2 in x 11.4 in) (LTEG23) • 68 mm x 64.7 mm x 208.7 mm (2.7 in x 2.5 in x 8.2 in) (LTEG23S)
Window Viewing Area (Ø)	• 62 mm (2.4 in), 30 mm (1.2 in) (dual glass) (LTEG23) • 40 mm x 40 mm (1.6 in x 1.6 in), 20 mm (0.8 in) (dual glass) (LTEG23S)
Operating Ambient Temperature	-
Bubble	-