

LTES06

V? camera b?ng thép không g? m? sau IP66



| | |
|--------------------------------|--|
| Model | LTES06 |
| Size (W x H x L) | 10.63 in <ul style="list-style-type: none"> 86 mm x 55 mm x 257 mm (3.39 in x 2.17 in x 10.12 in) (LTES06-R30-0) 108 mm x 250 mm (4.3 in x 9.8 in) (Ø x L) without internal bracket |
| Window Thickness | 8 mm (0.31 in) |
| Window Viewing Area (Ø) | <ul style="list-style-type: none"> 70 mm (2.76 in) 30 mm (1.18 in) (LTES06-R30-0, LTES06-L-R30-0) |
| Weight | <ul style="list-style-type: none"> 6.5 kg (14.33 lb) 8.4 kg (18.52 lb) (wall mount bracket included) 7 kg (15.43 lb) (LTES06-R30-0, LTES06-L-R30-0) 8.9 kg (19.62 lb) (wall mount bracket included) (LTES06-R30-0, LTES06-L-R30-0) |
| Material | <ul style="list-style-type: none"> AISI 304 stainless steel (LTES06, LTES06-R30-0) AISI 316L stainless steel (LTES06-L, LTES06-L-R30-0) |
| Cable Outlet | G-3/4" x 2 |
| Heater Control | On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) (optional) |
| Wavelength | 850 nm (LTES06-R30-0, LTES06-L-R30-0) |
| Illumination Distance | 30 m (98.43 ft) (LTES06-R30-0, LTES06-L-R30-0) |
| Beam Angle | 60° (LTES06-R30-0, LTES06-L-R30-0) |
| LEDs | 6 pieces (LTES06-R30-0, LTES06-L-R30-0) |
| LED Lifetime | > 25,000 hours (LTES06-R30-0, LTES06-L-R30-0) |
| Light On/Off | On when illumination is lower than 4 lux (LTES06-R30-0, LTES06-L-R30-0) |
| Related Products | - |

*Design and specifications are subject to change without prior notice.

Features

- IP68, NEMA-6P enclosure rating
- Operating temperature range from -25 °C to 60 °C (-13 °F to 140 °F)
- AISI 304/316L stainless steel construction (available)
- Built-in IR illuminator with distance up to 30 m (98.42 ft) (optional, input power: 12 V DC)

Available Models

| Model | Material | Illumination |
|----------------|----------|--------------|
| LTES06-0 | SS304 | |
| LTES06-R30-0 | SS304 | IR, 30 m |
| LTES06-L-0 | SS316L | |
| LTES06-L-R30-0 | SS316L | IR, 30 m |

Tech Specs

| | |
|--------------------------------------|---|
| Model | LTES06 |
| Type | Back opening |
| Atmospheric Pressure | 80 kPa to 106 kPa |
| Operating Ambient Temperature | -25 °C to 60 °C (-13 °F to 140 °F) |
| Relative Humidity | 5 % to 95 % noncondensing |
| Protection Rating | IP68, NEMA-6P enclosure rating |
| Input Power | 220 V AC, 50 Hz (optional) |
| Dimensions (W x H x L) | 140 mm x 140 mm x 348 mm (5.51 in x 5.51 in x 13.70 in) |
| Internal Usable | • 86 mm x 55 mm x 270 mm (3.39 in x 2.17 in x |