

# LTEV13

## V? camera nhôm khuôn ?úc m? bên IP66

K?t c?u nhôm khuôn ?úc, giá treo t??ng ?i kèm, kích th??c có th? s? d?ng bên trong (W x H x L): 120 mm x 90 mm x 320 mm



Model	Wiper	Heater	Blower	Input Power
LTEV13-W-0	+			
LTEV13-W-1-1	+	+		12 V DC
LTEV13-W-1-2	+	+		24 V AC
LTEV13-W-1-3	+	+		110 V AC
LTEV13-W-1-4	+	+		220 V AC
LTEV13-W-2-1	+		+	12 V DC
LTEV13-W-2-2	+		+	24 V AC
LTEV13-W-2-3	+		+	110 V AC
LTEV13-W-2-4	+		+	220 V AC
LTEV13-W-3-1	+	+	+	12 V DC
LTEV13-W-3-2	+	+	+	24 V AC
LTEV13-W-3-3	+	+	+	110 V AC
LTEV13-W-3-4	+	+	+	220 V AC
LTEV13-W-2-5	+		+	PoE

### Tech Specs

### Features

- IP66, NEMA-4P enclosure rating
- Designed for indoor and outdoor applications
- Input power: 12 V DC/24 V AC/110 V AC/220 V AC (available) or PoE (upgradable)
- Built-in heater and blower (optional)
- Built-in wiper (optional)
- Adjustable sliding camera tray
- Cable entry glands and mounting holes on bottom of housing
- Die-cast aluminum construction
- High impact resistance
- Bundled wall mount bracket

### Available Models

Model	Wiper	Heater	Blower	Input Power
LTEV13-0				
LTEV13-1-1		+		12 V DC
LTEV13-1-2		+		24 V AC
LTEV13-1-3		+		110 V AC
LTEV13-1-4		+		220 V AC
LTEV13-2-1			+	12 V DC
LTEV13-2-2			+	24 V AC
LTEV13-2-3			+	110 V AC
LTEV13-2-4			+	220 V AC
LTEV13-3-1		+	+	12 V DC
LTEV13-3-2		+	+	24 V AC
LTEV13-3-3		+	+	110 V AC
LTEV13-3-4		+	+	220 V AC
LTEV13-2-5			+	PoE

<b>Model</b>	LTEV13
<b>Type</b>	Indoor/Outdoor, side opening
<b>Protection Rating</b>	IP66, NEMA-4P enclosure rating
<b>Material</b>	Die-cast aluminum
<b>Finish</b>	White polyester powder coat
<b>Input Power</b>	<ul style="list-style-type: none"> <li>12 V DC (LTEV13-1-1, LTEV13-2-1, LTEV13-3-1, LTEV13-W-1-1, LTEV13-W-2-1, LTEV13-W-3-1)</li> <li>24 V AC (LTEV13-1-2, LTEV13-2-2, LTEV13-3-2, LTEV13-W-1-2, LTEV13-W-2-2, LTEV13-W-3-2)</li> <li>110 V AC (LTEV13-1-3, LTEV13-2-3, LTEV13-3-3, LTEV13-W-1-3, LTEV13-W-2-3, LTEV13-W-3-3)</li> <li>220 V AC (LTEV13-1-4, LTEV13-2-4, LTEV13-3-4, LTEV13-W-1-4, LTEV13-W-2-4, LTEV13-W-3-4)</li> <li>PoE (IEEE 802.3at Class 4 PoE Plus compliant) (LTEV13-2-5, LTEV13-W-2-5)</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>Heater (12 V DC/24 V AC/110 V AC/ 220 V AC): 30 W</li> <li>Blower: 2 W (167 mA)</li> </ul>
<b>Network Interface</b>	RJ-45 x 2 (PoE input/data output) (LTEV13-2-5, LTEV13-W-2-5)
<b>Dimensions (W x H x L)</b>	170 mm x 127.5 mm x 500 mm (6.7 in x 5.0 in x 19.7 in)
<b>Window Viewing Area (W x H)</b>	94 mm x 70 mm (3.7 in x 2.8 in)
<b>Window Thickness</b>	3 mm (0.12 in), tempered glass
<b>Internal Usable Size (W x H x L)</b>	120 mm x 90 mm x 320 mm (4.7 in x 3.5 in x 12.6 in)
<b>Heater Control</b>	On at 0 °C ± 3 °C (32 °F ± 5 °F), off at 5 °C ± 3 °C (41 °F ± 5 °F) ( LTEV13-1-1, LTEV13-1-2, LTEV13-1-3, LTEV13-1-4, LTEV13-3-1, LTEV13-3-2, LTEV13-3-3, LTEV13-3-4, LTEV13-W-1-1, LTEV13-W-1-2, LTEV13-W-1-3, LTEV13-W-1-4, LTEV13-W-3-1, LTEV13-W-3-2, LTEV13-W-3-3, LTEV13-W-3-4)
<b>Blower Control</b>	On at 45 °C ± 3 °C (113 °F ± 5 °F), off at 35 °C ± 3 °C (95 °F ± 5 °F) ( LTEV13-2-1, LTEV13-2-2, LTEV13-3-2, LTEV13-2-4, LTEV13-3-1, LTEV13-3-2, LTEV13-3-3, LTEV13-3-4, LTEV13-2-5, LTEV13-W-2-1, LTEV13-W-2-2, LTEV13-W-3-2, LTEV13-W-2-4, LTEV13-W-3-1, LTEV13-W-3-2, LTEV13-W-3-3, LTEV13-W-3-4, LTEV13-W-2-5)
<b>Operating Ambient Temperature</b>	-40 °C to 60 °C (-40 °F to 140 °F)
<b>Weight</b>	<ul style="list-style-type: none"> <li>3.1 kg (6.8 lb)</li> <li>Max. 3.8 kg (8.4 lb) (wall mount bracket included)</li> </ul>
<b>Certifications</b>	CE, FCC, RoHS
<b>Related Products</b>	-

\*Design and specifications are subject to change without prior notice.