

# LTEV15

## V? camera quét dòng IP66



|   |  |
|---|--|
| <b>Model</b>                            | <b>LTEV15</b>  |
| <b>Area (W x H)</b>                     |  |
| <b>Window Thickness</b>                 | 3 mm (0.12 in), tempered glass   |
| <b>Internal Usable Size (W x H x L)</b> | 160 mm x 136 mm x 357 mm (6.3 in x 5.7 in x 14.1 in) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)  |
| <b>Heater Control</b>                   | On at 15 °C ± 3 °C (59 °F ± 5 °F), off at 25 °C ± 3 °C (77 °F ± 5 °F) ( LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)  |
| <b>Blower Control</b>                   | On at 40 °C ± 3 °C (104 °F ± 5 °F), off at 30 °C ± 3 °C (86 °F ± 5 °F) ( LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)   |
| <b>Operating Ambient Temperature</b>    | -40 °C to 60 °C (-40 °F to 140 °F) ( LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)   |
| <b>Weight</b>                           | <ul style="list-style-type: none"> <li>• 4 kg (8.8 lb) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)</li> <li>• Max. 4.7 kg (10.4 lb) (wall mount bracket included) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)</li> </ul> |
| <b>Certifications</b>                   | CE, FCC, RoHS  |
| <b>Related Products</b>                 | -  |

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-4X enclosure rating
- Designed for indoor and outdoor applications
- Included sunshield
- Input power: 12 V DC/24 V AC/220 V AC (available)
- Adjustable sliding camera tray

### Available Models

| Model      | Heater | Blower | Input Power |
|------------|--------|--------|-------------|
| LTEV15-3-1 | +      | +      | 12 V DC     |
| LTEV15-3-2 | +      | +      | 24 V AC     |
| LTEV15-3-4 | +      | +      | 220 V AC    |

### Tech Specs

|                               |  |
|-------------------------------|--|
| <b>Model</b>                  | <b>LTEV15</b>  |
| <b>Type</b>                   | Indoor/Outdoor, side opening, for lin scan camera  |
| <b>Protection Rating</b>      | IP66, NEMA-4X enclosure rating   |
| <b>Material</b>               | Aluminum   |
| <b>Finish</b>                 | White polyester powder coat  |
| <b>Input Power</b>            | <ul style="list-style-type: none"> <li>• 12 V DC (LTEV15-3-1)</li> <li>• 24 V AC (LTEV15-3-2)</li> <li>• 220 V AC (LTEV15-3-4)</li> </ul>                    |
| <b>Output Power</b>           | -  |
| <b>Power Consumption</b>      | <ul style="list-style-type: none"> <li>• Heater (12 V DC): 4.2 W (350 mA) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)</li> <li>• Blower: 1.68 W (140 mA)</li> </ul> |
| <b>Dimensions (W x H x L)</b> | 162 mm x 166 mm x 486.5 mm (6.4 in x 6.5 in x 19.2 in) (LTEV15-3-1, LTEV15-3-2, LTEV15-3-4)  |
| <b>Window Viewing</b>         | -  |