

# LTPD01

V? camera quay quét PTZ d?ng vòm ngoài tr?i

12.7 cm (5 in), PTZ speed dome housing



<b>Model</b>	<b>LTPD01</b>
<b>Protocols</b>	Pelco-D, Pelco-P
<b>Communication Speed</b>	2,400 bps, 4,800 bps, 9,600 bps adjustable
<b>Standard Setting</b>	Available with BNC cable
<b>OSD menu</b>	Available
<b>Preset</b>	Up to 226 preset positions, 8 scanning modes
<b>Surge Protection</b>	-
<b>Dimensions (W x H x L)</b>	262 mm x 382.7 mm x 150 mm (10.3 in x 15.1 in x 5.9 in)
<b>Weight</b>	3 kg (6.61 lb)
<b>Wavelength</b>	850 nm
<b>Illumination Distance</b>	100 m (328.1 ft)
<b>Beam Angle</b>	-
<b>LEDs</b>	9 pieces
<b>LED Lifetime</b>	> 25,000 hours
<b>Light On/Off</b>	On when illumination is lower than 4 lux
<b>Note</b>	-

\*Design and specifications are subject to change without prior notice.

## Features

- IP66, NEMA-6P enclosure rating
- Die-cast aluminum construction

## Tech Specs

<b>Model</b>	LTPD01
<b>Type</b>	Indoor/Outdoor
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	Die-cast aluminum
<b>Finish</b>	White
<b>Input Power</b>	12 V DC
<b>Power</b>	50 W
<b>Consumption</b>	
<b>Pan Range (Movement in Horizontal Plane)</b>	0° to 360° continuous
<b>Pan Speed</b>	0° to 300° per second
<b>Tilt Range (Movement in Vertical Plane)</b>	-45° to 45°
<b>Tilt Speed</b>	0 to 270° per second
<b>Accuracy</b>	0.225° ± 0.003°
<b>Atmospheric Pressure</b>	-
<b>Operating Ambient Temperature</b>	-10 °C to 50 °C (-14 °F to 122 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Communication</b>	RS-485