

# LTPD02

## V? PTZ d?ng vòm ngoài tr?i

20.8 cm (8.2 in), V? PTZ d?ng vòm



<b>Model</b>	<b>LTPD02</b>
<b>Speed</b>	
<b>Standard Setting</b>	Available with BNC cable
<b>OSD menu</b>	Available
<b>Preset</b>	Up to 160 preset positions, 1 scanning modes, 4 tracks (path record), 8 patro groups (each patrol group patrol point 2 to 64)
<b>Surge Protection</b>	-
<b>Dimensions (W x H x L)</b>	208 mm x 433 mm x 278 mm (8.2 in x 17.0 in x 10.9 in)
<b>Internal Usable Size (W x H x L)</b>	55 mm x 60 mm x 120 mm (2.2 in x 2.4 in x 4.7 in)
<b>Weight</b>	3 kg (6.6 lb)
<b>Wavelength</b>	850 nm
<b>Illumination Distance</b>	2 m to 120 m (6.6 ft to 393.7 ft), 1 way short distance, 2 way long distance LED
<b>Beam Angle</b>	-
<b>LEDs</b>	9 pieces
<b>LED Lifetime</b>	> 25,000 hours
<b>Light On/Off</b>	On when illumination is lower than 4 lux
<b>Note</b>	-

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-6P enclosure rating
- Die-cast aluminum construction

### Tech Specs

<b>Model</b>	<b>LTPD02</b>
<b>Type</b>	Indoor/Outdoor
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	Die-cast aluminum, ABS
<b>Finish</b>	White
<b>Input Power</b>	12 V DC
<b>Power</b>	30 W maximum
<b>Consumption</b>	
<b>Pan Range (Movement in Horizontal Plane)</b>	0° to 360° continuous
<b>Pan Speed</b>	0.5 to 160° per second
<b>Tilt Range (Movement in Vertical Plane)</b>	0° to 90°
<b>Tilt Speed</b>	0.5 to 30° per second
<b>Accuracy</b>	0.1°
<b>Atmospheric Pressure</b>	-
<b>Operating Ambient Temperature</b>	-10 °C to 50 °C (-14 °F to 122 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Communication Protocols</b>	RS-485, LAN
<b>Communication</b>	Pelco-D (9600 bps), 2,400 bps, 4,800 bps, 9,600 bps adjustable