

# LTPM04

B? Pan tilt ngoài tr?i t?i tr?ng lên ??n 15 kg (33.1 lb)

IP66, t?i tr?ng l?n nh?t 15 kg (33.1 lb), t?c ?? có th? ?i?u ch?nh, c?u trúc h?p kim nhôm



<b>Model</b>	<b>LTPM04</b>
<b>Consumption</b>	
<b>Pan Speed</b>	0.4° to 10° per second
<b>Pan Range</b>	0° to 360° continuous
<b>(Movement in Horizontal Plane)</b>	
<b>Tilt Speed</b>	0.4° to 2.5° per second
<b>Tilt Range</b>	• -60° to 10° for load 20 kg (44.1 lb) (factory setting)
<b>(Movement in Vertical Plane)</b>	
<b>Accuracy</b>	0.4°
<b>Operating Ambient Temperature</b>	-40 °C to 70 °C (-40 °F to 158 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Communication</b>	RS-485
<b>Protocols</b>	Pelco-D, Pelco-P
<b>Baud Rate</b>	2,400/4,800/9,600 bps adjustable
<b>Standard Setting</b>	• Available with BNC Cable (LTPM04-A-6, LTPM04S-A-6) • Available with network cable (100Mbps) (LTPM04-N-6, LTPM04S-N-6)
<b>OSD menu</b>	Available
<b>Heater</b>	Optional
<b>Dimensions (W x H x L)</b>	• 301 mm x 217 mm x 184 mm (11.9 in x 8.5 in x 7.2 in) (LTPM04-A-6, LTPM04S-A-6) • 610 mm x 217 mm x 184 mm (24.0 in x 8.5 in x 7.2 in) (LTPM04-N-6, LTPM04S-N-6)
<b>Weight</b>	9.3 kg (20.5 lb)
<b>Note</b>	-

\*Design and specifications are subject to change without prior notice.

## Features

- IP66, NEMA-6P enclosure rating
- Maximum load 15 kg (33.1 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)

## Available Models

Model	Load	Support	Input Power
LTPM04-A-6	Top load	Analogue	24 V DC
LTPM04-N-6	Top load	Network	24 V DC
LTPM04S-A-6	Side load	Analogue	24 V DC
LTPM04S-N-6	Side load	Network	24 V DC

## Tech Specs

<b>Model</b>	<b>LTPM04</b>
<b>Maximum Load</b>	15 kg (33.1 lb)
<b>Type</b>	Indoor/Outdoor, top load (LTPM04-A-6, LTPM04-N-6), side load (LTPM04S-A-6, LTPM04S-N-6)
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	Aluminum alloy
<b>Finish</b>	Beige
<b>Input Power</b>	24 V DC
<b>Power</b>	40 W