

# LTPM05

## B? ph?n Pan Tilt ngoài tr?i

Pan-tilt ngoài tr?i t?i tr?ng lên ??n 15kg(33.1lb)



<b>Model</b>	<b>LTPM05</b>
<b>Horizontal Plane)</b>	
<b>Tilt Range</b>	-75° to 40° (-90° to 40° optional)
<b>(Movement in Vertical Plane)</b>	
<b>Accuracy</b>	0.225° ± 0.003°
<b>Operating Ambient Temperature</b>	-35 °C to 65 °C (-31 °F to 149 °F)
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Auto Scan</b>	Up to 5 lines, based on OSD function, configurable speed
<b>Auto Cruise</b>	Up to 8 groups, based on OSD function, configurable speed
<b>Continuous Scan</b>	8 line, configurable speed and angles
<b>Angles Display</b>	Support
<b>Communication</b>	RS-485
<b>Protocols</b>	Pelco-D, Pelco-P
<b>Baud Rate</b>	2,400/4,800/9,600/19,200 bps adjustable
<b>Standard Setting</b>	<ul style="list-style-type: none"> <li>Available with BNC Cable (<b>LTPM05-A</b>)</li> <li>Available with network cable (100Mbps) (<b>LTPM05-N</b>)</li> </ul>
<b>OSD menu</b>	Available
<b>Preset</b>	Up to 80
<b>Lens Drivien</b>	10 V/6 V software control and adaptive
<b>Lens Interface</b>	Support (pan and tilt preset configuration interface)
<b>Surge Protection</b>	GB/T17626.5-2008
<b>Dimensions (W x H x L)</b>	249 mm x 230 mm x 302 mm (9.80 in x 9.06 in x 11.89 in)
<b>Weight</b>	15 kg (33.1 lb)
<b>Note</b>	-

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-4X enclosure rating
- Maximum load 15 kg (33.1 lb)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Input power: 24 V AC
- Support analogue or network cameras (optional)

### Available Models

Model	Support
LTPM05-A	Analogue
LTPM05-N	Network

### Tech Specs

Model	LTPM05
<b>Maximum Load</b>	15 kg (33.1 lb)
<b>Type</b>	Indoor/Outdoor, top load
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	Aluminum alloy
<b>Finish</b>	Beige
<b>Input Power</b>	24 V AC ± 25 %
<b>Power</b>	max. 85 W (heater off), max. 95 W (heater on)
<b>Consumption</b>	
<b>Pan Speed</b>	0.01° to 60° per second
<b>Tilt Speed</b>	0.01° to 30° per second
<b>Pan Range (Movement in</b>	0° to 360° continuous