

LTPM11

B? Pan tilt ngoài tr?i t?i tr?ng lên ??n 9 kg (19.8 lb)

IP66, t?i tr?ng l?n nh?t 9 kg (19.8 lb), t?c ?? có th? ?i?u ch?nh, c?u trúc h?p kim nhôm



Model	LTPM11
Temperature	
Relative Humidity	5 % to 95 % noncondensing
Communication	RS-485
Protocols	Pelco-D, Pelco-P
Baud Rate	2,400/4,800/9,600 bps adjustable
Standard Setting	Available with BNC cable and network cable
Dimensions (W x H x L)	223 mm x 350 mm x 250 mm (8.8 in x 13.8 in x 9.8 in)
Packing Dimensions (W x H in x L)	340 mm x 310 mm x 820 mm (13.4 in x 12.2 in x 32.3 in)
Weight	10 kg (22.0 lb)

*Design and specifications are subject to change without prior notice.

Features

- IP66, NEMA-4X enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)

Tech Specs

Model	LTPM11
Maximum Load	9 kg (19.8 lb)
Type	Indoor/Outdoor
Protection Rating	IP66, NEMA-4X enclosure rating
Material	High-strength aluminum
Finish	Beige
Input Power	24 V DC/24 V AC
Power	60 W (heater: 25 W), standby max. 15 W
Consumption	
Pan Speed	0.1° to 100° per second
Pan Range	0° to 360° continuous
(Movement in Horizontal Plane)	
Tilt Speed	0.1° to 100° per second
Tilt Range	-90° to 40°
(Movement in Vertical Plane)	
Accuracy	0.1°
Operating Ambient	-30 °C to 60 °C (-22 °F to 140 °F)