

LTSU06

B? Pan tilt ngoài tr?



Model	LTSU06
Baud Rate	2,400/4,800/9,600 bps adjustable
Standard Setting	Available with BNC cable and network cable
Surge Protection	Built-in lightning and surge protection
Internal Usable Size (W x H x L)	74 mm x 90 mm x 160 mm (2.9 in x 3.5 in x 6.3 in) (single side)
Dimensions (W x H x L)	250 mm x 472 mm x 360 mm (9.8 in x 18.6 in x 14.2 in)
Weight	20 kg (44.1 lb)
Wavelength	-
Illumination	-
Distance	-
Beam angle	-

*Design and specifications are subject to change without prior notice.

Features

- IP67, NEMA-6P enclosure rating
- High-strength aluminum construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Wiper included
- Support analogue or network cameras (optional)

Tech Specs

Model	LTSU06
Type	Indoor/Outdoor
Protection Rating	IP67, NEMA-6P enclosure rating
Material	High-strength aluminum
Finish	Beige
Input Power	24 V AC/24 V DC
Power Consumption	60 W (heater: 25 W), standby max. 15 W
Pan Speed	0.1° to 100° per second
Pan Range (Movement in Horizontal Plane)	0° to 360° continuous
Tilt Speed (Movement in Vertical Plane)	0.1° to 100° per second
Tilt Range	-90° to 40°
Accuracy	0.1°
Operating Ambient Temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Relative Humidity	5 % to 95 % noncondensing
Communication Protocols	RS-485 Pelco-D, Pelco-P