

# LTSV02

## Cameraa quay quét PTZ ánh sáng tr?ng ch?ng rung

IP66, thi?t k? ch?ng rung phù h?p ?? s? d?ng trên xe, chi?u sáng b?ng ánh sáng tr?ng v?i kho?ng cách lên ??n 400 m (1312,3 ft), bao g?m c?n g?t n??c



<b>Model</b>	<b>LTSV02</b>
<b>Accuracy</b>	0.225° ± 0.003°
<b>Atmospheric Pressure</b>	80 kPa to 106 kPa
<b>Relative Humidity</b>	5 % to 95 % noncondensing
<b>Operating Ambient Temperature</b>	-35 °C to 65 °C (-31 °F to 149 °F)
<b>Communication</b>	RS-485
<b>Protocols</b>	Pelco-D/Pelco-P
<b>Baud Rate</b>	2,400/4,800/9,600/19,200 bps adjustable
<b>Dimensions (W x H x L)</b>	235 mm x 176 mm x 375 mm (9.25 in x 6.93 in x 14.76 in)
<b>Weight</b>	7.2 kg (15.87 lb)
<b>Colour</b>	6000 K
<b>Wavelength</b>	-
<b>Illumination Distance</b>	400 m (1312.3 ft)
<b>Beam angle</b>	6° to 60°

\*Design and specifications are subject to change without prior notice.

### Features

- IP66, NEMA-6P enclosure rating
- Anti-vibration design suitable for vehicle use
- Built-in white light illuminator with distance up to 400 m (1312.3 ft)
- Pan and tilt speed adjustable
- Wiper included

### Tech Specs

<b>Model</b>	<b>LTSV02</b>
<b>Type</b>	Indoor/Outdoor, anti-vibration
<b>Protection Rating</b>	IP66, NEMA-4X enclosure rating
<b>Material</b>	High-strength aluminum
<b>Finish</b>	Silver
<b>Input Power</b>	10.5 V DC to 18 V DC (3.5 A)
<b>Power Consumption</b>	28 W
<b>Pan Range (Movement in Horizontal Plane)</b>	0° to 360° continuous
<b>Pan Speed</b>	<ul style="list-style-type: none"> <li>▪ 0° to 80° per second adjustable</li> <li>▪ Preset speed: 0° to 80° per second adjustable</li> </ul>
<b>Tilt Range (Movement in Vertical Plane)</b>	-90° to 90°
<b>Tilt Speed</b>	<ul style="list-style-type: none"> <li>▪ 0° to 40° per second adjustable</li> <li>▪ Preset speed: 100° per second</li> </ul>