

LTEG23

IP66 Bullet Housing for Camera Module

| | |
|-------------------------|---|
| Model | LTEG23 |
| Size (W × H × L) | (LTEG23) <ul style="list-style-type: none"> • 40 mm × 34 mm × 97 mm (1.6 in × 1.5 in × 3.8 in) (LTEG23S) |
| Related Products | - |
| Weight | <ul style="list-style-type: none"> • 0.98 kg (2.2 lb) (LTEG23) • 0.4 kg (0.9 lb) (LTEG23S) |
| Certifications | RoHS |

*Design and specifications are subject to change without prior notice.



Features

- IP66, NEMA-4X enclosure rating
- Designed for indoor and outdoor applications
- Die-cast aluminum construction
- Compact size (selectable)

Available Models

| Model | Dimension |
|----------------|---|
| LTEG23 | 93 mm × 80.6 mm × 290 mm (3.7 in × 3.2 in × 11.4 in) |
| LTEG23S | 68 mm × 64.7 mm × 208.7 mm (2.7 in × 2.5 in × 8.2 in) |

Tech Specs

| Model | LTEG23 |
|--------------------------------------|--|
| Type | Indoor/Outdoor, bullet type |
| Protection Rating | IP66, NEMA-4X enclosure rating |
| Material | Die-cast aluminum |
| Finish | White polyester powder coat |
| Input Power | - |
| Dimensions (W × H × L) | <ul style="list-style-type: none"> • 93 mm × 80.6 mm × 290 mm (3.7 in × 3.2 in × 11.4 in) (LTEG23) • 68 mm × 64.7 mm × 208.7 mm (2.7 in × 2.5 in × 8.2 in) (LTEG23S) |
| Window Viewing Area (Ø) | <ul style="list-style-type: none"> • 62 mm (2.4 in), 30 mm (1.2 in) (dual glass) (LTEG23) • 40 mm × 40 mm (1.6 in × 1.6 in), 20 mm (0.8 in) (dual glass) (LTEG23S) |
| Operating Ambient Temperature | - |
| Bubble | - |
| Internal Usable | • 57 mm × 48 mm × 155 mm (2.2 in × 1.9 in × 6.1 in) |