

# LTIL04

## Infrared Laser Illuminator

Illumination distance up to 2,000 m (6,562 ft)



### Features

- Illuminator with distance up to 2,000 m (6,562 ft)
- Motor driven beam angle from 0.8° to 72° adjustable
- Synchronized with camera zoom
- Input power: 12 V DC
- Semi-covert (808 nm) wavelength

### Tech Specs

<b>Model</b>	LTIL04
<b>Input Power</b>	12 V DC
<b>Power</b>	40 W
<b>Consumption</b>	
<b>Dimensions (W x H x L)</b>	64 mm x 63 mm x 147 mm (2.5 in x 2.5 in x 5.8 in)
<b>Operating Ambient Temperature</b>	-20 °C to 50 °C (-4 °F to 122 °F)
<b>Storage Temperature</b>	-40 °C to 80 °C (-40 °F to 176 °F)
<b>Weight</b>	550 g (1.2 lb)
<b>Wavelength</b>	808 ± 5 nm
<b>Beam Angle</b>	0.8° to 72°, motor driven
<b>Illumination Distance</b>	up to 2,000 m (6,562 ft)
<b>Laser Lifetime</b>	30,000 hours
<b>Communication</b>	RS485, TTL232

\*Design and specifications are subject to change without prior notice.