

LTPM06U

Outdoor Pan and Tilt Unit (Triple mount, Analogue/Network, 60° per second)

IP66, maximum load of 25 kg (55.1 lb), speed adjustable pan and tilt, aluminum alloy construction, analogue, 60° per second



Features

- IP66, NEMA-6P enclosure rating
- Maximum load 50 kg (110.2 lb)
- Maximum pan speed 30° per second/60° per second (optional)
- Aluminum alloy construction
- Designed for indoor and outdoor applications
- Pan and tilt speed adjustable
- Support analogue or network cameras (optional)
- Input power: 24 V AC/24 V DC

Available Models

| Model | Support | Type | Max. Speed |
|----------|------------------|-------------|----------------|
| LTPM06-A | Analogue | Top Load | 30° per second |
| LTPM06-N | Network | Top Load | 30° per second |
| LTPM06U | Analogue/Network | Triple Load | 60° per second |

Tech Specs

| Model | LTPM06 |
|-------------------|--|
| Maximum Load | <ul style="list-style-type: none"> • 50 kg (110.2 lb) (LTPM06-A, LTPM06-N) • 25 kg (55.1 lb) (LTPM06U) |
| Type | <ul style="list-style-type: none"> • Indoor/Outdoor, top load (LTPM06-A, LTPM06-N) • Indoor/Outdoor, triple load (LTPM06U) |
| Protection Rating | IP66, NEMA-4X enclosure rating |
| Material | Aluminum alloy |

| | |
|--------------------------------|--|
| Model | LTPM06 |
| Finish | Beige polyester powder coat |
| Input Power | 24 V AC/ 24 V DC |
| Power Consumption | <ul style="list-style-type: none"> • 85 W maximum (LTPM06-A, LTPM06-N) • 120 W maximum (LTPM06U) |
| Pan Speed | <ul style="list-style-type: none"> • 0.01° to 30° per second (LTPM06-A, LTPM06-N) • 0.01° to 60° per second (LTPM06U) |
| Pan Range | 0° to 360° continuous |
| (Movement in Horizontal Plane) | |
| Tilt Speed | <ul style="list-style-type: none"> • 0.01° to 15° per second (LTPM06-A, LTPM06-N) • 0.01° to 30° per second (LTPM06U) |
| Tilt Range | <ul style="list-style-type: none"> • -45° to 45° for load 50 kg (110.2 lb) (factory setting) • -60° to 60° for load 40 kg (88.2 lb) • -80° to 80° for load 26 kg (57.3 lb) (for triple load) • -90° to 90° for double load |
| (Movement in Vertical Plane) | |
| Accuracy | 0.225° ± 0.003° |
| Operating Ambient Temperature | -35 °C to 65 °C (-31 °F to 149 °F) |
| Relative Humidity | 5 % to 95 % noncondensing |
| Auto Scan | Up to 8 lines, based on OSD function, configurable speed |
| Auto Cruise | Up to 8 groups, based on OSD function, configurable speed |
| Keep Watch | Programmed a preset, an auto scan line or an auto cruise group, based on OSD function, dwell time counting down display |
| Helix Scan | 8 line, configurable speed and angles |
| Continuous Scan | 8 line, configurable speed and angles |
| Angles Display | Real-time on screen display/Response by query command |
| Communication | RS-485, RS-422 |
| Protocols | Pelco-D, Pelco-P |
| Baud Rate | 2,400/4,800/9,600/19,200 bps adjustable |
| Standard Setting | <ul style="list-style-type: none"> • Available with BNC Cable (LTPM06-A, LTPM06U) • Available with network cable (100Mbps) (LTPM06-N, LTPM06U) |
| OSD menu | Available |
| Preset | Up to 80 |
| Lens Driven | 10 V/6 V software control and adaptive |
| Lens Interface | Support (pan and tilt preset configuration interface) |
| Surge Protection | GB/T17626.5-2008 |
| Dimensions (W × H × L) | 342 mm × 403 mm × 224 mm (13.5 in × 15.9 in × 8.8 in) |
| Weight | <ul style="list-style-type: none"> • 27 kg (59.5 lb) (LTPM06-A, LTPM06-N) • 32 kg (70.5 lb) (LTPM06U) |
| Note | - |

*Design and specifications are subject to change without prior notice.